

Qlikview v10 file handling

New document	<i>Ctrl+N</i>
Open Document	<i>Ctrl+O</i>
Open Document on server	<i>Ctrl+Shift+N</i>
Save Document	<i>Ctrl+S</i>
Save Document as	<i>F12</i>

Qlikview v10 selection keys

Open Current Selections view	<i>ctrl + Q</i>
Back in selections	<i>shift + leftarrow</i>
Forward in selections	<i>shift + rightarrow</i>
Lock the object selection	<i>ctrl + L</i>
Lock all selections	<i>ctrl + shift + L</i>
Ulock the object selection	<i>ctrl + U</i>
Unlock all selections	<i>ctrl + shift + U</i>
Clear (Delete) the object selection	<i>ctrl + D</i>
Clear (Delete) all selections	<i>ctrl + shift + D</i>

Qlikview v10 edit shortcut keys

Undo layout change	<i>Ctrl + Z</i>
Redo layout change	<i>Ctrl + Y</i>
Cut	<i>Ctrl + X</i>
Copy	<i>Ctrl + C</i>
Paste	<i>Ctrl + V</i>
Remove	<i>Del</i>
Activate All	<i>Ctrl + A</i>
Find	<i>Ctrl + F</i>
Advanced Find	<i>Shift + Ctrl + F</i>

Qlikview v10 F Keys

Activates context sensitive help	<i>F1</i>
Enters search mode	<i>F3</i>
Activates the sheet tab to the left of the active one	<i>F6</i>
Activates the leftmost tab	<i>ctrl + F6</i>
Activates the sheet tab to the right of the active one	<i>F7</i>

Qlikview v10 F Keys (cont)

Activates the rightmost tab	<i>ctrl + F7</i>
Save as	<i>F12</i>

Qlikview v10 actions keys

Print document	<i>ctrl + P</i>
Print as PDF	<i>ctrl + shift + P</i>
Edit script	<i>ctrl + E</i>
Reload data	<i>ctrl + R</i>
Partial reload data	<i>ctrl + shift + R</i>
Table viewer	<i>ctrl + T</i>
Show/Hide grid	<i>ctrl + G</i>
Open User Preferences	<i>ctrl + alt + U</i>
Open Document Properties	<i>ctrl + alt + D</i>
Open Sheet Properties	<i>ctrl + alt + S</i>
Open Variable Overview	<i>ctrl + alt + V</i>
Open Expression Overview	<i>ctrl + alt + E</i>
Properties of the selected object(s)	<i>alt + enter</i>
Edit Module	<i>ctrl + M</i>
Alerts	<i>ctrl + alt + A</i>
Add Bookmark	<i>ctrl + B</i>
More Bookmark	<i>ctrl + shift + B</i>

Qlikview v10 set analysis identifiers

0	Empty set
1	Full set of all the records
\$	Current selection
\$1	Previous selection
\$_1	Forward selection
Bookmark01	Bookmark ID or name

Qlikview v10 set analysis operators

+	Union
-	Exclusion (first but not the other)
*	Intersection (both)
/	Symmetric difference (either but not both)

Qlikview v10 set analysis modifiers

<OrderDate = DeliveryDate>	Select only data where field1 = field2
<Field = {value}>	Select specific value
<Region = >	Ignore the specific field
<Year={2000}, Region = {"U*"}>	Two fields can be filtered, with wildcards

Qlikview v10 script edition keys


Go to line number in the script	<i>ctrl + G</i>
List of keyboard shortcuts	<i>ctrl + Q,S,C</i>
Comment lines in script	<i>ctrl + K,C</i>
Uncomment lines in script	<i>ctrl + K,U</i>
Add tab in script	<i>ctrl + Q,T,A</i>
Promote active tab	<i>ctrl + Q,T,P</i>
Demote active tab	<i>ctrl + Q,T,D</i>
Rename active tab	<i>ctrl + Q,T,N</i>
Remove active tab	<i>ctrl + Q,T,R</i>
Creates an autogenerated script	<i>ctrl + Q,Q</i>
Opens Unicode input utility	<i>ctrl + Q,U,I</i>
Creates a script for reading jpg attributes	<i>ctrl + Q,J,P,G</i>
Creates a script for reading mp3 attributes	<i>ctrl + Q,M,P,3</i>
Creates a script for reading wma attributes	<i>ctrl + Q,W,M,A</i>

ctrl + K,C means *ctrl + K* then *ctrl + C*



Qlikview v10 set analysis examples

<code>sum(sales) or sum({\$} sales)</code>	sales in current selection
<code>sum({1} sales) or sum({1} Total sales)</code>	sales disregarding the selection <i>or</i> disregarding selection and dimension
<code>sum({\$<OrderDate = DeliveryDate>} sales)</code>	sales in current selection for a specific date
<code>sum({1<Region = {US}>} sales)</code>	total sales for region=US
<code>sum({<Region = > sales})</code>	sales in selection with region removed (idem \$)
<code>sum({\$<Year={2000}, Region = {"U*"}>} sales)</code>	current selection but year forced to 2000 and region like U*
<code>sum({\$<Year = {\$(vLastYear)}>} sales)</code>	sales related to a variable
<code>p({<Year={\$(=max(Y- ear)-1)}>} customer)</code>	returns customers who are possible for last year
<code>e({<Year={\$(=max(Y- ear)-1)}>} customer)</code>	returns customers who are excluded for last year



By **Frederic Villemin** (fredv)
cheatography.com/fredv/
www.tasteofindie.com

Published 6th November, 2011.
Last updated 12th May, 2016.
Page 2 of 2.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>