

Constants: Basic Constants

domain	To globally change your domain (to go live for example)
protocol	Globally change your protocol. e.g. from http:// to https://
fileadmin	change the basic path to your fileadmin directory (<i>fileadmin/old_files</i> to <i>fileadmin/new_files</i>)

TypoScript: Basic Configuration

```

config {
doctype = html5
xmlprologue = none
baseURL = {$protocol}://{domain}
language = de
locale_all = german
htmlTag_langKey = de
sys_language_uid = 0
# Add L Parameter to links
linkVars := addToList(L)
uniqueLinkVars = 1
# Enable ReaURL
tx_realurl_enable = 1
# Decide for yourself
moveJsFromHeaderToFooter = 0
# AdminPanel on
admPanel = 1
# Pagetitle off
noPageTitle = 2
# Spam-Protection - choose your favorite method
spamProtectEmailAddresses = ascii
}

```

TypoScript: Change Website Title

```

page.headerData {
10 = TEXT
10 {
field = title
noTrimWrap = |<title>| - Website</title>|
}
}

config.noPageTitle = 2
is mandatory

```

TypoScript: Fav Icon

```
page.shortcutIcon = {fileadmin}/favicon.ico
```

TypoScript: Language Condition

```

[globalVar = GP:L = 1]
config.sys_language_uid = 1
config.language = en
config.locale_all = english
config.htmlTag_langKey = en
[global]

```

TypoScript: Add Meta-Tag "viewport"

```
page.meta.viewport = width=device-width,
initial-scale=1, maximum-scale=1, user-
scalable=no
```

TypoScript: Canonical-Tag

```

page.headerData.930 = TEXT
page.headerData.930 {
typolink {
parameter = {page:uid}
parameter.insertData = 1
useCacheHash = 1
addQueryString = 1
addQueryString.method = GET
addQueryString.exclude =
id,no_cache,tt_news[backPid]
returnLast = url
}
wrap = <link rel="canonical" href="
{$protocol}://{domain}" />
}

```

TypoScript: Backend Layout

```

page.10 = FLUIDTEMPLATE
page.10 {
# Use the constants in your tpls
variables {
domain = TEXT
domain.value = {domain}
protocol = TEXT
protocol.value = {protocol}
fileadmin = TEXT
fileadmin.value = {fileadmin}
# e.g. for anchor urls
typo3_request_url = TEXT
typo3_request_url.data = getIndpEnv:
TYPO3_REQUEST_URL

```

TypoScript: Backend Layout (cont)

```

}
file.stdWrap.cObject = CASE
file.stdWrap.cObject {
key.data = levelfield:-1,
backend_layout_next_level, slide
key.override.field = backend_layout
# default template file
default = TEXT
default.value = {fileadmin}/tpl/default.html
2 = TEXT
2.value = {fileadmin}/tpl/alt_one.html
3 = TEXT
3.value = {fileadmin}/tpl/alt_two.html
}
}

```



By **achjaderleon**

cheatography.com/achjaderleon/

Published 13th November, 2012.

Last updated 22nd November, 2012.

Page 1 of 1.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>