Cheatography

JavaScript: Basic, Advanced, & More Cheat Sheet

by AC Winter (acwinter) via cheatography.com/21349/cs/4084/

About This Document

the purpose of this cheat sheet is to briefly describe the core elements of the JavaScript language for those of studying it who have taken in much more than we can hold onto well. nothing here is explained *in full* but rather meant to get you on the right track. also, this document purposely does not cover browser-specific methods / syntax / objects and the like.

this cheat sheet is a work in progress and may be updated -- check back on occasion!

Types

Type	typeOf evaluation	Primitive?
Null	object	yes
Undefined	undefined	yes
Boolean	boolean	yes
String	string	yes
Number	number	yes
Object	object	no -- *an object*
Function	function	no -- *an object*
Array	object	no -- *an object*
Symbol	symbol	no -- *an object*
[]	object	no -- *an object*
{}	object	no -- *an object*

Number & Math Methods

» `someNu m.t oFi xed (num)`

• shortens someNum to have only num decimal places

» `num.to Exp one ntial()`

• converts num to exponential notation (i.e. 5.569e+0)

» `num.to Str ing()`

• converts num to a string

» `num.to Pre cis ion(#)`

• converts num to a num with # places starting with whole numbers

» `String (so meV alue)`

• converts or coerces someValue to a string - someValue can be any type, ie "Boolean(1)" returns true

» `parseI nt( string, radix)`

» `parseF loa t(s tring, radix)`

• converts a string into an integer. the optional radix argument defines the base -- i.e., base 10 (decimal) or base 16 (hexadecimal).

» `Math.r oun d(num)`

• rounds num to nearest integer

Number & Math Methods (cont)

» `Math.c eil (num)`

• rounds num *up* to nearest integer

» `Math.f loo r(num)`

• rounds num *down* to nearest integer

» `Math.m ax( num1, num2)`

• returns larger num

» `Math.m in( num1, num2)`

» `Math.p ow( num1, num2)`

• returns num1 to the power num2

» `Math.s qrt (num)`

» `Math.r andom()`

• returns decimal between 0 (inclusive) and 1(exclusive)

» `Math.a bs(num)`

• returns absolute value of num•

Array "Extra Methods"

Note: these "extra methods," which are "higher-order" functions, ignore holes in the array (i.e.: [“apples”, , , , “oranges”]). they also have more arguments than shown here -- best to look them up for more info!

Note: array-*like* objects, for example `arguments` and `NodeLists`, can also make use of these methods.

» `arr.so me( cal lback)`

» `arr.ev ery (ca llback)`

• returns a boolean value. returns true if *some* or *every* element in the array meets the evaluation. example:

```
var a = [1,2,3];
var b = a.ever y(f unc tio n(i tem){
      return item > 1;
}); // false
```

» `arr.re duc e(f unc tio n(prev, next){..}, startVa l)`

» `arr.re duc eRi ght (fu nct ion (prev, next){..}, startVal)`

• returns a value. *reduce* employs a callback to run through the elements of the array, returning "prev" to itself with each iteration and taking the next "next" value in the array. for it's first "prev" value it will take an optional "startVal" if supplied. an interesting example:

```
var arr = ["ap ple ", " pea r", " app le", " lem - on"];
var c = arr.re duc e(f unc tio n(prev, next) {
 prev[next] = (prev[ next] += 1) || 1;
 return prev;
```


Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Array "Extra Methods" (cont)

```
}, {});
// objCount = { apple: 2, pear: 1, lemon: 1 }
```

» arr.fi lte r(f unc tio n() {..})

• returns an array. *filter* returns an array of elements that satisfy a given callback. example:

```
var arr2 = ["ji m", " nan cy", " ned "];
var letter3 = arr2.f ilt er( fun cti on( item) {
 return (item.l ength === 3);
});
consol e.l og( let ter3); // ['jim', 'ned']
```

» arr.so rt(fun cti on( ){..})

• returns *the original* array, mutated. *sort* returns the elements sorted with a given criteria. for example:

```
var stock = [{key: "r", num: 12}, {key: "a", num: 2}, {key: "c", num: 5}];
var c = stock.s or t(f unc tio n(a,b) {
 return a.num - b.num;
} ); // [ { key: 'a', num: 2 }, { key: 'c', num: 5 }, { key: 'r', num: 12 } ]
```

» arr.map()

• returns an array. *map* goes over every element in the array, calls a callback on the element, and sets an element in the new array to be equal to the return value the callback. for example:

```
var stock = [{key: " red ", num: 12}, {key: " blu e", num: 2}, {key: " bla ck", nu
m: 2}];
var b = stock.m ap (fu nction (item){
 return item.key;
}) // ["re d","b lue " ,"bl ack "]
```

» arr.fo rEach()

• no return value. *forEach* performs an operation on all elements of the array. for example:

```
var arr = ["jim", "mary"];
a.forEach (function (item) {
  consol e.l og( "I simply love " +item);
}); // "I simply love jim", "I simply love mary"
```

Note: you can combine array methods in a *chain* where the result of the leftmost operation is passed to the right as such:

```
array.s or t().re ver se()...
```

Functions & Etc.

Callbacks: placing ( ) after a function call *executes it immediately.* lea for a callback.

Function Declaration

» function aFunct ionName (args) {...

• functions created in this manner are evaluated when the code is parse the top and are available to the code *even before* they're formally decla odd construction, using function declarations within a flow control stater and is best avoided.

Function Expression / Anonymous Functions

» var bar = function (args) {...

• (also referred to as 'Function Operators') anonymous functions are ev and are therefore less memory intensive. they must be provided a varia have a function name (therefore: anonymous). [these are]

Named Function Expression

» var bar = function foo (args) {...

• confusingly, this is still an 'anonymous function.' assigning a name is u purposes and also allows for self-referential / recursive calls

Function Constructor

» var anothe rFu nction = new Function (args, funct ..}

• equivalent to a functional expression

Self-Invoking Anonymous Functions

» (function (args) { doSome thing; }) ( );

• (also known as IIFEs / 'Immediately Invoked Function Expressions') a ately

Loops / Control Flow Statements

if .. else if .. else

```
if (consi dtion1) {
     doSome thing;
} else if {
     doSome thi ngElse;
} else {
     doSome thi ngMore;
}
```

for loop

```
for (var i = 0; i < someNu mber; i++) {
    doSome thing;
}
```

switch loop

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Loops / Control Flow Statements (cont)

```
switch (someE val uation) {
    case " eva lua tes AsT his " :
         doSome thing;
    case " eva lua tes AsT hat " :
         doSome thi ngElse;
}
```

while loop

```
while (someE val uation === true) {
    doSome thing;
}
```

do .. while

```
do {
    doSome thing;
}
while (someE val uation === true);
```

for .. in (objects)

```
for (anItem in anObject) {
     doSome thing With anItem;
   // will be the key
     doSome thi ngWith Object [an Item];
   // will be the value of that key
}
```

"this"

coming soon

String Methods, Properties & Etc

a string *can be coerced into an array* so many array methods are applicable as well

» `str.ch arA t(num)`
• returns the character in str at index num
» `str.ch arC ode At(num)`
• returns the unicode value of the char
String.fromCharCode(num)`
• returns the character with unicode's num
» `str.in dex Of( char)`
• returns -1 if char not found in str
» `str.la stI nde xOf (su bSt ring)`

String Methods, Properties & Etc (cont)

• returns the index of the last occurrence of subString
» `str.length`
• returns length of str starting at 1
» `str.ma tch (pa ttern)`
• returns null if not found. returns an *array* of all matches
» `str.ma tch (/p att ern/g)`
• provides global search of string
» `str.re pla ce(old, new)`
» `str.se arc h(p attern)`
• returns index of first match or -1 if not found
» `str.su bst rin g(i ndex1, index2)`
• char at index1 is returned, index2 is not
» `str.sp lit (char)`
• returns an array of str split on char
» `str.su bst r(i ndex1, num)`
• returns substring starting at index1 and running num letters
» `str.to Low erC ase()`
» `str.to Upp erC ase()`
» `str.to Loc ale Low erC ase()`
• takes local language settings into account
» `str.to Loc ale Upp erC ase()`
• ibid
» `Number (va r/s tri ng/ object)`
• converts to number. "true" converts to 1, etc
» `one.co nca t(two)`
• concatenates string/array one with two
» `JSON.s tri ngify( )`
• converts a javascript value/object into a string
» `JSON.parse ( )`
• converts a JSON string into a javascript object

Date Methods

Note: Unix epoch is January 1, 1970
» `var today = new Date();`
• creates date object for now
» `var someDate = new Date("june 30, 2035");`
• creates date object for arbitrary date
» `var today = Date.n ow();`

By **AC Winter** (acwinter)
cheatography.com/acwinter/

Published 6th May, 2015.
Last updated 9th May, 2016.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Date Methods (cont)

• returns number of milliseconds since epoch

» `parse()`

• returns milliseconds between date and Unix epoch.

» `toDate Str ing()`

» `toTime Str ing()`

» `toLoca lTi meS tring()`

Get / Set Date Methods

• getDate()	• getHours()
• getDay()	• getMilliseconds()
• getFullYear()	• getMinutes()
• getMonth()	• getSeconds()
• getTime()	• getTimezoneOffset()

Note: there are also 'set' methods such as *setMonth()*.

Note: getDay and getMonth return numeric representations starting with 0.

Miscellaneous Instructions

» `break;`

• breaks out of the current loop

» `continue;`

• stops current loop iteration and increments to next

» `isNaN( som eVar)`

• returns true if not a number

» `isFini te( som eVar)`

» `var aVar = anObje ct[ anA ttr ibute] || " non esu ch";`

• assigns a default value if none exists

» `var aVar = anEval uation ? trueVal : falseVal;`

• ternary operator. assigns trueVal to aVar if anEvaluation is true, falseVal if not

» `delete anObje ct[ anA ttr ibute]`

» `(aProperty in anObject)`

• returns true or false if aProperty is a property of anObject

» `eval(s ome String)`

• evaluates a someString as if it was JavaScript. i.e. eval("var x = 2+3") returns 5

Array Methods (basic)

Note: index numbers for arrays start at 0

» `arr.le ngth()`

» `arr. push(val)`

• adds val to end of arr

» `arr. pop()`

• deletes last item in arr

» `arr. shift()`

• deletes first item in arr

» `arr.un shi ft(val)`

• adds val to front of arr

» `arr.re verse ()`

» `arr1.c onc at( arr2)`

• concatenates arr1 with arr2

» `arr.jo in( char)`

• returns string of elements of arr joined by char

» `arr.sl ice (in dex1, index2)`

• returns a new array from arr from index1 (inclusive) to index2 (exclusive)

» `arr.sp lic e(i ndex, num, itemA, itemB,..)`

• alters arr. starting at index and through index+num, overwrites/adds itemsA..

Definitions & Lingo

Higher Order Functions

> functions that accept *other functions* as an argument

Scope

> the set of variables, objects, and functions available within a certain block of code

Callback

> (also *event handler*) a reference to executable code, or a piece of executable code, that is passed as an argument to other code.

the % operator

> % returns the remainder of a division such that "3 % 2 = 1" as 2 goes into 3 once leaving 1. called the "remainder" or "modulo" operator.

Composition

> the ability to assemble complex behaviour by aggregating simpler behavior. *chaining* methods via dot syntax is one example.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com

Definitions & Lingo (cont)

Chaining

also known as *cascading*, refers to repeatedly calling one method after another on an object, in one continuous line of code.

Naming Collisions

where two or more identifiers in a given namespace or a given scope cannot be unambiguously resolved

DRY

Don't Repeat Yourself

ECMAScript

(also *ECMA-262*) the specification from which the JavaScript implementation is derived. version 5.1 is the current release.

Arity

refers to the number of arguments an operator takes. ex: a binary function takes two arguments

Currying

refers to the process of transforming a function with multiple arity into the same function with less *arity*

Recursion

an approach in which a function calls itself

Predicate

a calculation or other operation that would evaluate either to "tru-e" or “false.”

Asynchronous

program flow that allows the code following an *asynchronous* statement to be executed immediately without waiting for it to complete first.

Callback Hell

code thickly nested with callbacks within callback within callbacks.

Closure

a function with access to the global scope, it's parent scope (if there is one), and it's own scope. a closure may retain those scopes even after it's parent function has *returned.*

IIFE

Immediately Invoked Function Expressions. *pronounced "iffy."* a function that is invoked immediately upon creation. employs a unique syntax.

Definitions & Lingo (cont)

Method

an object property has a function for its value.

Reserved Words

abstract	arguments	boolean	break
byte	case	catch	char
class	const	continue	debugger
default	delete	do	double
else	enum	eval	export
extends	false	final	finally
float	for	function	goto
if	implements	import	in
instanceof	int	interface	let
long	native	new	null
package	private	protected	public
return	short	static	super
switch	synchronized	this	throw
throws	transient	true	try
typeof	var	void	volatile
while	with	yield	

Prototype-based Inheritance

coming soon

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com