## Keyboard Shortcuts

| | |
|---|---|
| Ctrl + p | Open Channel / User search |
| Up Arrow | Edit previous message |
| Command (or Alt) + Left Arrow | Move to the beginning of the message |
| Command (or Alt) + Up Arrow | Move to the beginning of the message |
| Command (or Alt) + Right Arrow | Move to the end of the message |
| Command (or Alt) + Down Arrow | Move to the end of the message |
| Shift + Enter | New line in message compose input |

## Slash Commands

| | |
|---|---|
| /kick @username | Remove someone from the room |
| /archive #channel | Archive |
| /leave | Leave the current channel |
| /join #channel) | Join the five channel |
| /create channel | Create a new channel |
| /invite @username | Invite one user to join this channel |
| /me your message | Displays action text |
| /mute @username | Mute someone in the room |
| /open room name | Opens a channel, group or direct message |

## Hubot Commands

| | |
|---|---|
| ! help | Displays all of the help commands that Hubot knows about. |
| ! help <query> | Displays all help commands that match <query>. |
| ! create standup hh:mm | Creates a standup at hh:mm every weekday for this room |
| ! create standup hh:mm at location/url | Creates a standup at hh:mm (UTC) every weekday for this chat room with a reminder for a physical location or url |
| ! delete standup hh:mm | If you have a standup on weekdays at hh:mm, delete it. Can also supply a weekday and/or UTC offset |
| ! echo <text> | Reply back with <text> |
| ! hello | <what the respond trigger does> |
| ! map me <query> | Returns a map view of the area returned by `query`. |
| ! standup help | See a help document explaining how to use. |
| ! time | Reply with current time |
| ! translate me <phrase> | Searches for a translation for the <phrase> and then prints that bad boy out. |
| ! translate me from <source> into <target> <phrase> | Translates <phrase> from <source> into <target>. Both <source> and <target> are optional |

## Gitlab Commands

| | |
|---|---|
| ! gitlab list projects | list projects |
| ! gitlab list users | list users |
| ! gitlab show project <id> | shows details about a project |
| ! gitlab show project keys <id> | shows the keys on a project |
| ! gitlab show user <id> | shows details about a user |

## Jenkins Commands

| | |
|---|---|
| ! jenkins b <jobNumber> | builds the job specified by jobNumber. List jobs to get number. |
| ! jenkins build <job> | builds the specified Jenkins job |
| ! jenkins build <job>, <params> | builds the specified Jenkins job with parameters as key=value&key2=value2 |
| ! jenkins describe <job> | Describes the specified Jenkins job |
| ! jenkins last <job> | Details about the last build for the specified Jenkins job |
| ! jenkins list <filter> | lists Jenkins jobs |

## Jira Commands

| | |
|---|---|
| ! jl prefixes | Responds with the configured Jira project prefixes to build URLs for e.g. "DEV" for DEV |
| ! jl url | Responds with the configured Jira base URL |