

Variables

```
$cool-red: #F44336;
h1.title {
  color: $cool-red;
}
```

Mixins

A mixin lets you make groups of CSS declarations that you want to reuse throughout your site. You can even pass in values to make your mixin more flexible.

i.e. in scss file:

```
@mixin border-radius($radius) {
  border-radius: $radius;
}
.box { @include border-radius(10px); }
```

i.e. in sass file:

```
=border-radius($radius)
-webkit-border-radius: $radius
-moz-border-radius: $radius
-ms-border-radius: $radius
border-radius: $radius
```

```
.box
+border-radius(10px)
```

@media

Used to define different style rules for different media types/devices in SASS

i. e.: @media (min-width: 768px) { p { font-size: 18px; } }

i. e.: @media (min-width: 768px) and (max-width: 1023px) { p { font-size: 18px; } }

@import

Use To import file or solder inside SCSS and SASS

i. e.:

To import _reset.scss into _reset.scss
@import 'reset';



By **Ahmed Yahia** (Ahmed.Yahia)
cheatography.com/ahmed-yahia/
www.ahmedyahia.com

Not published yet.
Last updated 29th September, 2016.
Page 1 of 1.

Sponsored by **Readability-Score.com**
Measure your website readability!
<https://readability-score.com>