

Uses

```
format!("Hello {}", " World! "); // Returns a
formatted string from a fmtstr.
let mut vec = vec![""];
// Destination (first arg) must &impl mut
io::Write or a &impl mut fmt::Write
write!(&mut vec, " Hello {}", " World! "); //
Writes a fmtstr
writeln!(&mut vec, " Hello Me!"); // writeln! but
appends a newline
println!("Hello {}", " World! "); // Prints a
fmtstr to stdout
println! (" Hello {}", " World! "); // println! but
appends a newline
eprintln!("Hello {}", " World! "); // Prints a
fmtstr to stderr
eprintln! ("Hello {}", " World! "); // eprintln!
but appends a newline
format! _ar gs! ("Hello {}", " World! "); //
Returns fmt::A rgu ments, see https://docs.rs -
t-1 ang.org/s td/ fmt /#f orm at\_args
```

Referencing Arguments

{}	Next positional argument ¹
{n}	n-th positional argument, starting from 0
{ident}	"ident" named argument, if nonexistent "ident" variable from the scope
{{	Literal {
}}	Literal }

¹ Ex. The second usage of {} would be the second positional argument.

Specifying Arguments

All format macros start with a format string, with the exception of `writeln!` and `writeln!` requiring a additional destination argument. It can contain a number of formats specified below. Positional arguments are specified immediately after, and then named arguments in the `ident = val` format.



By [ambi \(ambiguous\)](#)
cheatography.com/ambiguous/

Not published yet.
 Last updated 19th November, 2023.
 Page 1 of 1.

Sponsored by [CrosswordCheats.com](#)
 Learn to solve cryptic crosswords!
<http://crosswordcheats.com>