

### Basic Commands

<code>iwconfig</code>	Show wireless interfaces
<code>iwlist</code>	Show informations about wireless interfaces
<code>iwlist wlan0 scanning</code>	Show information about wireless networks next to interface
<code>iwconfig wlan0 channel &lt;n&gt;</code>	Change the channel of interface wlan0 to <n>
<code>iwconfig wlan0 down</code>	Disables wlan0 interface
<code>iwconfig wlan0 up</code>	Enables wlan0 interface
<code>iwconfig wlan1 mode &lt;Ad-Hoc Auto Managed Master Monitor Repeater Secondary&gt;</code>	Change mode of interface wlan0

### Aircrack-ng basic

<code>airmon-ng check kill</code>	Disabel all process that could causa troubles in wifi hacking
<code>airmon-ng start wlan0</code>	Put wlan0 interface on monitor mode
<code>airmon-ng stop wlan0mon</code>	Put wlan0 interface back to normal
<code>airodump-ng wlan0mon</code>	Start packet capture on wlan0mon
<code>airodump-ng wlan0mon --channel &lt;n&gt; --essid &lt;Wifi-Name&gt;</code>	Filter packter capture with channel and Wifi ESSID
<code>airodump-ng wlan0mon --channel &lt;n&gt; --essid &lt;Wifi-Name&gt; -w &lt;filename&gt;</code>	Record packet capture in <filename>
<code>airodump-ng -r file.pcap</code>	Reads file.pcap as in airodump-ng
<code>aireplay-ng --deauth &lt;n&gt; -a &lt;BSSID&gt; wlan1mon</code>	Send DoS attack on BSSID with n packets. 0 means infinity loop.



By **astronaut3301**

Not published yet.

Last updated 27th March, 2022.

Page 1 of 1.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>