

## lib/action\_view/helpers/date\_helper.rb

```
def datetime_select      Then $ rails s (restart server)
  binding.pry
```

```
f.datetime_select      fstarts_at
<select>
```

```
def time_select
  binding.pry
```

```
f.time_select          fstarts_at
<input> X 3
<select> X 2
```

## lib/action\_view/helpers/form\_options\_helper.rb

```
d collection_select    Then $ rails s (restart server)
  binding.pry
```

```
f.collection_select
<select>
```

```
d select
  binding.pry
```

```
f.select              fassignee_id, fhow_heard, fstatus, ftransaction-
<select>              _type
```

```
d time_zone_select
  binding.pry
```

```
f.time_zone_select    ftime_zone
<select>
<option> X N
```

## actiontext/app/helpers/action\_text/tag\_helper.rb

```
def rich_text_area_tag  Then $ rails s (restart server)
  binding.pry
```

```
f.rich_text_area_tag  fcontent
```

## turbo-rails/app/helpers/turbo/frames\_helper.rb

```
def turbo_frame_tag      Then $ rails s (restart server)
  binding.pry
```

```
f.turbo_frame_tag
<turbo-frame>
```

## Snippets

routes.rb

r

xxxxx\_controller.rb

```
controller          class PluralController
```

```
ci or cindex        def index
```

```
cs or cshow         def show
```

```
cn or cnew          def new
```

```
cc or ccreate       def create
```

```
ce or cedit         def edit
```

```
cu or cupdate       def update
```

```
cd or cdestroy      def destroy
```

```
cni or cnindex      def index (nested)
```

```
cns or cnshow       def show (nested)
```

```
cnn or cnnew        def new (nested)
```

```
cnc or cncreate     def create (nested)
```

```
cne or ccredit      def edit (nested)
```

```
cnu or cnupdate     def update (nested)
```

```
cnd or cdestroy     def destroy (nested)
```



By **baxter2**  
[cheatography.com/baxter2/](https://cheatography.com/baxter2/)

Not published yet.  
Last updated 28th February, 2023.  
Page 1 of 1.

Sponsored by **Readable.com**  
Measure your website readability!  
<https://readable.com>