

File Type Navigation Commands

:Econtroller	:Scontroller
:Scontroller events	:Scontroller events/registrations
:Scontroller events#index	:Scontroller events#show
:Scontroller events:15	:Scontroller events/upcoming!
:Scontroller events!	:Scontroller events/registrations!
:Senvironment	:Senvironment development
:Senvironment procs	:Senvironment test
:Sfixtures	
:Sfunctionaltest	
:Shelper	
:Sinitializer	:Sinitializer inflections
:Sinitializer lograge!	
:Sintegrationtest	
:Sjavascript	
:Slayout	
:Slib	
:Sspec	
:Slocale	
:Smailer	
:Smigration	Smigration regis
:Smodel	:Smodel <C-a> <C-a>
:Smodel event!	
:Smigration	
:Smodel	
:Sschema	

gf or C-w f (* indicates cursor position)

```
Pos*t.first
app/models/post.rb

has_many :c*omments
app/models/comment.rb

link_to 'Home', :controller => 'bl*og'
app/controllers/blog_controller.rb

<%= render 'sh*ared/sidebar' %>
app/views/shared/_sidebar.html.erb

<%= stylesheet_link_tag 'appl*ication' %>
app/assets/stylesheets/application.css

class BlogController < Applica*tionController
app/controllers/application_controller.rb

class ApplicationController < ActionCont*roller::Base
.../action_controller/base.rb

fixtures :pos*ts
test/fixtures/posts.yml

layout :pri*nt
app/views/layouts/print.html.erb

<%= link_to "New", new_comme*nt_path %>
app/controllers/comments_controller.rb (jumps to def new)
```

In the last example, the controller and action for the named route are determined by evaluating routes.rb as Ruby and doing some introspection. This means code from the application is executed. Keep this in mind when navigating unfamiliar applications.

Snippet Rails

```
routes.rb

r

XXXXX_controller.rb

ci || cindex          def index
cni || cnindex       def index (nested)
cs || cshow          def show
cns || cnshow        def show (nested)
cn || cnew            def new
cnn || cnnew         def new (nested)
cc || ccreated        def create
cnc || cncreate      def create (nested)
ce || cedit           def edit
cne || ccredit        def edit (nested)
cu || cupdate         def update
cnu || cnupdate       def update (nested)
cd || cdestroy        def destroy
cnd || cndestroy      def destroy (nested)
```

:Sstylesheet

:Stask

:Sunittest

:Sview index.html.erb :Sview index.htm.erb!

:Sview events/upcoming/index.ht- :Sview layouts/_footer.ht-
ml.erb ml.erb!

Each of the following commands has variants for splitting, vertical splitting, opening in a new tab, and reading the file into the current buffer. For :Emodel, those variants would be :Smodel, :Vmodel, :Tmodel, and :Dmodel.



By **baxter2**
cheatography.com/baxter2/

Not published yet.
Last updated 16th November, 2022.
Page 1 of 2.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>