

### Edit

- gS** to split a one-liner into multiple lines
- gJ** (with the cursor on the first line of a block) to join a block into a single-line statement.

### NORMAL Navigation

- %** Jump to matching brace/parenthesis
- }** Jump down to next empty line
- {** Jump up to next empty line
- ]]** Jump down to next `module` or `class` definition
- [[** Jump up to next `module` or `class` definition
- ]m** Jump down to next `def`
- [m** Jump up to next `def`
- ]M** Jump down to next `end`
- [M** Jump up to next `end`
- vim**  $\vee$  `LINE` inside current method definition
- vam**  $\vee$  `LINE` around current method definition

### surround ragtag

Mapping	Changed to (cursor = ^)
<C-S>=	<% = ^ %>
<C-S>-	<% ^ %>
<C-X>=	foo<% = ^ %>
<C-X>-	foo<% ^ %>
<C-X>+	<% = foo^ %>
<C-X>_	<% foo^ %>

The table above shows what happens if the binding is pressed at the end of a line consisting of "foo".



By [baxter2](#)  
[cheatography.com/baxter2/](https://cheatography.com/baxter2/)

Not published yet.  
 Last updated 28th February, 2023.  
 Page 1 of 1.

Sponsored by [Readable.com](#)  
 Measure your website readability!  
<https://readable.com>