

### Artisan

```
php artisan routes
```

```
php artisan controller:make UserController
```

### // Migrations

```
php artisan migrate:make create_users_table
```

```
php artisan migrate:make create_users_table --create=users
```

```
php artisan migrate
```

```
php artisan migrate:rollback
```

```
php artisan migrate:refresh
```

### // Seed

```
php artisan generate:seed posts
```

```
php artisan db:seed
```

```
php artisan migrate:refresh --seed
```

```
php artisan db:seed --class=PostsTableSeeder
```

### // Generators

```
php artisan generate:resource post --fields="title:string, body:text"
```

```
php artisan generate:pivot categories users
```

### Migrations

```
...
public function up(){
    Schema::create('users', function(Blueprint $table){
        $table->increments('id');
        $table->integer('role');
        $table->string('email')->unique();
        $table->string('password', 60);
        $table->rememberToken();
        $table->timestamps;
    });
}
public function down(){
    Schema::drop('users');
}
...
```

### Seeds (faker)

```
...
User::create([
    'email' => $faker->email(),
    'password' => $faker-> md5()
]);
...
```

### Routes

#### Ruta simple

```
Route::get('/',function(){
    return View::make('hello');
});
```

#### Ruta amb paràmetres

```
Route::get('posts/{id}',function($id){
    return View::make('post.single')->with('id', $id);
});
```

#### Ruta Controlador + mètode

```
Route::get('post', 'PostController@show');
```

#### Ruta nominal

```
Route::get('post/all', array('uses' => 'PostController@all', 'as' =>
    'post.all');
```

#### Ruta + validació RegEX

```
Route::get('post/{id}', array('uses' => 'PostController@single', 'as' =>
    'get.post.single'))->where('id', '[1-9][0-9]*');
```

#### Ruta POST

```
Route::post('post', array('uses' => 'PostController@create', 'as' =>
    'post.post.create');
```

#### Ruta Resource

```
Route::resource('post', 'PostController');
Route::resource('post', 'PostController', array('except' => 'show'));
Route::resource('post', 'PostController', array('only' => 'show'));
```

#### Filtres

```
Route::get('post/create', array('uses' => 'PostController@create', 'as'
    => 'post.create', 'before' => 'auth'));
```

#### Grups

```
Route::group(array('before' => 'auth'), function(){
    // Route:: ...
    // Route:: ...
});
```



By **bernattorras**

Published 9th October, 2014.

Last updated 13th May, 2016.

Page 1 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

### Routes (cont)

```
});  
Prefixs  
Route::group(array('prefix' => 'admin'), function(){  
// Route:: ...  
// Route:: ...  
});
```

### Blade functions

```
@if(count($posts))  
@foreach($posts as $post)  
<p>{{{ $post->title }}} </p>  
@endforeach  
@endif
```

### Blade Layout

```
<!-- HTML -->  
@include('partials.menu');  
[...]  
@yield('content');  
[...]  
@section('sidebar');  
[...]  
@show
```

### Blade Template

```
@extends('layouts.default');  
@section('content');  
[...]  
@stop  
@section('sidebar')  
@parent  
[...]  
@stop
```

### Query Builder

```
// SELECT  
$users = DB::table('users')->get();  
$users = DB::table('users')->find(2);  
$users = DB::table('users')->where('id',2)->get();  
$users = DB::table('users')->where(array('id' => 2, 'email' => 'test@-  
test.com'))->get();  
$users = DB::table('users')->where('id',2)->orWhere('id', 3)->get();  
$users = DB::table('users')->where(array('id' => 2, 'email' => 'test@-  
test.com'))->get();  
$users = DB::table('users')->where('id', '>', 1)->orderBy('id', 'asc')->t-  
ake(2)->skip(2)->get();  
$users = DB::table('users')->join('posts', 'users.id', '=', 'posts.user_-  
id')->get();  
// Log  
dd(DB::getQueryLog());  
// INSERT  
$data = array(  
'email' => 'bernat.torras@uvic.cat',  
'password' => '123456'  
);  
DB::table('users')->insert($data);  
// UPDATE  
$data = array(  
'email' => 'bernat.torras@uvic.cat',  
'password' => 'abc'  
);  
DB::table('users')->where('email', $data['email'])->update($data);  
// DELETE  
DB::table('users')->where('email', 'bernat.torras@uvic.cat')->delete();
```

### Eloquent ORM

```
// SELECT  
$posts = Post::all();  
$posts = Post::find(2);  
$posts = Post::where('title', 'LIKE', '%et%')->get();  
$posts = Post::where('title', 'LIKE', '%et%')->take(1)->skip(1)->get();  
// INSERT  
$post = new Post;  
$post->title = 'post1 title';  
$post->body = 'post1 body';
```



By **bernattorras**

Published 9th October, 2014.  
Last updated 13th May, 2016.  
Page 2 of 3.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>

### Eloquent ORM (cont)

```
$post->save();  
// Insert amb vector de dades  
$data = array(  
    'title' => 'post2 title',  
    'body' => 'post2 body'  
);  
Post::create($data);  
// UPDATE  
$post = Post::find(1);  
$post->title('updated title');  
$post->save();  
// DELETE  
$post = Post::find(1);  
$post->delete();
```

### Relacions BDD (Model)

```
class Post extends \Eloquent {  
    ...  
    public function user(){  
        return $this->belongsTo("User");  
    }  
    // hasMany  
    // hasOne  
    // belongsToMany  
}  
...  
}
```



By **bernattorras**

[cheatography.com/bernattorras/](http://cheatography.com/bernattorras/)

Published 9th October, 2014.

Last updated 13th May, 2016.

Page 3 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>