

TextBox

Get Value	<code>\$("#id").val()</code>
Set Value	<code>\$("#id").val("new value")</code>
Enable	<code>\$("#id").prop("disabled",false);</code>
Disable	<code>\$("#id").prop("disabled",true);</code>
Hide	<code>\$("#id").hide()</code>
Show	<code>\$("#id").show()</code>
On Lost Focus	<code>\$("#id").on('change', function)</code>
On Lost Focus	<code>\$("#id").change(function)</code>
On Focus	<code>\$("#id").focus(function)</code>
Set Focus	<code>\$("#id").focus()</code>
On Change (via keyboard)	<code>\$("#id").on('keyup paste mouseup', function)</code>
Add Class	<code>\$("#id").addClass("something")</code>
Remove Class	<code>\$("#id").removeClass("something")</code>
Get Length	<code>\$("#id").val().length</code>

Checkbox

Check if checked	<code>\$("#id").is(":checked")</code>
Check if not checked	<code>\$("#id").is(":not(:checked)")</code>
Set Checkbox	<code>\$("#id").prop("checked", true)</code>
Unset Checkbox	<code>\$("#id").prop("checked", false)</code>
Disable, enable, add class, remove class is the same as textbox	

Select Box

Selected (hidden) Value	<code>\$("#id").val();</code>
Text of selected option	<code>\$("#id option:selected").text()</code>
On selecting an option	<code>\$("#id").change(function)</code>
Select an option using code	<code>\$("#id").val(3);</code>
Disable a single option	<code>\$("#id option[value='3']").attr("disabled", true);</code>
Enable a single option	<code>\$("#id option[value='3']").attr("disabled", false);</code>

Bootstrap Modal

Multiselect Modal

SPL Date Time

Radio List

TextArea

Alerts and Ask Value

Alert

```
bootbox.alert("message")
```

Confirm

```
bootbox.confirm("question",function (r) { if (r) dosomething } )
```

Grid / Table

Remove Row

Ajax

Get record

Save record

Delete record



By **blinkdata**
cheatography.com/blinkdata/

Not published yet.
 Last updated 13th May, 2016.
 Page 1 of 1.

Sponsored by **CrosswordCheats.com**
 Learn to solve cryptic crosswords!
<http://crosswordcheats.com>