

PostgreSQL

Common Data Types:

INTEGER, FLOAT

VARCHAR(n): varying length character string of maximum length n

DATE: A date attribute in a DBMS-specific format.

Sample Use Case:

Create a table of students holding student IDs and names. Create another table that shows which student IDs are taking which courses:

```
CREATE TABLE Student(id INTEGER,
name VARCHAR(20));
```

```
CREATE TABLE Takes(id INTEGER,
course VARCHAR(20));
```

Data Manipulation

Add a new student:

```
INSERT INTO Student (id, name) VALUES
(003841201, 'Zingaro', 'Daniel');
```

Update rows in a table (set a certain student's name based on id):

```
UPDATE Student SET name = "Gilfoyle"
WHERE id = '1337';
```

Delete students named "Bob Jones" from the table:

```
DELETE FROM Student WHERE name =
'Bob Jones';
```

Find everyone taking CSC309:

```
SELECT name FROM Student, Takes
WHERE Student.id = Takes.id AND
Takes.course = 'CSC309';
```

PHP commands

```
$conn = $db_connect("$connect_string");
```

PostgreSQL (cont)

```
$result = $pg_query($conn, $query);
while ($row = $pg_fetch_array($result)) { do
something }
```

If we're going through a list of students, \$row[id] is equivalent to Student.id in above example.

HTTP Commands

```
<!-- GET a specified resource,
DELETE a specified resource,
HEAD get the response headers
(without associated data), PUT
accompanying data at the
specified location, POST
accompanying data as a
subordinate to the specified
location. !-->
```

AUTHENTICATION REQUEST

```
GET /~arno ld/ 309 /ph ttp /he -
llo.html HTTP/1.1
Host: www.cs.toronto.edu
Authorization: Basic YXJub2 -
xkO nByb2Y=
YXJub2 xkO nByb2Y is a Base64
encoding of userid :pa ssword.
```

CSS Example

```
// selected navigation bar, do
stuff to it
nav {
position:
absolute; top: 52px; left:0;
width: 160px; height: 700px;
}
// now each individual button
nav a {
display: block;
border-color: blue;
```

CSS Example (cont)

```
> border-style: solid;
background-color: #ACE;
text-align: center;
white-space: nowrap;
padding: 10px;
margin-bottom: 0.25em;
color:black;
}
```

Vote App (vote.js - Express)

```
require('./static-
content/lib/constants.js'); //
defines wwPort and wwWsPort
var express = require('exp -
ress');
var app = express();
var votes = { yes:0 , no:0 } ;
// Web sockets to broadcast
results
var WebSocketServer = require -
('ws').Server
, wss = new WebSocketSer -
ver ({port: wwWsPo rt});
wss.on ('close', function() {
console.log('di -
sconnected');
});
wss.broadcast = functi on(){
for(let ws of
this.clients){
ws.send(JSON.stringify(v -
otes));
}
}
wss.on ('connection',
function(ws) {
ws.send(J -
SON.stringify(votes));
});
```

Vote App (vote.js - Express) (cont)

```
> var bodyParser = require('body-parser');
app.use(bodyParser.json()); // support json
encoded bodies
app.use(bodyParser.urlencoded({ extended:
true })); // support encoded bodies
app.use(express.static('static-content'));
app.put('/api/vote/:value/', function (req, res)
{
var voteValue = req.params.value;
if(voteValue=="yes")votes.yes++;
if(voteValue=="no")votes.no++;

console.log("PUT:"+voteValue);
console.log("Total Votes so far:"+votes);
var result = { result: "ok" , currentVotes:
votes};
console.log(JSON.stringify(result));
res.json(result);
wss.broadcast();
});
app.listen(wwPort, function () {
console.log('Example app listening on port
'+wwPort);
});
```

Vote App (vote.html - React, Sockets, REST)

```
<script type="text/javascript">

var socket;

$(function(){

/

/ socket = new WebSoc ket -
("ws :// csl inu x.u tm.u to -
ron to.c a: 100 01");
```

Vote App (vote.html - React, Sockets, REST) (cont)

```
> alert(global.wwWsURL);

socket = new WebSoc-
ket(global.wwWsURL);

socket.onopen =

function (event) {

console.log("con-
nected");

};

socket.onclose =

function (event) {

alert("closed
code:" + event.code + " reason:"
+event.reason + " wasClean:"+event.wasCl-
ean);

};

socket.onmessage =

function (event) {

var votes=JSO-
N.parse(event.data);
$("#VoteCount").html("Yes:"+votes.yes+" "-
+"No:"+votes.no);

};

</script>

<script type="text/javascript">
function sendVote(vote){
$.ajax({
method: "PUT",
url: "/api/vote/"+vote
}).done(function(data){
console.log("Got back:"+JSON.s-
tringify(data));
});
}
</script>

<script type="text/babel">
class VoteButton extends React.Com-
ponent {
```

Vote App (vote.html - React, Sockets, REST) (cont)

```
> constructor(props) {
super(props);
}
render(props){
return (
<button onClick={this.props.clickHandler} >
{ this.props.label } </button>
);
}
}
class VoteComponent extends React.Com-
ponent {
constructor(props) {
super(props);
this.state = { }
this.yesClickHandler = this.yesClickHandl-
er.bind(this);
this.noClickHandler = this.noClickHandler.b-
ind(this);
}
yesClickHandler(e){
sendVote("yes");
console.log("yes");
}
noClickHandler(e){
sendVote("no");
console.log("no");
}
render(){
```



By **bogoSort**

cheatography.com/bogosort/

Not published yet.

Last updated 14th April, 2018.

Page 2 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Vote App (vote.html - React, Sockets, REST) (cont)

```
> return (
<div style={{border:"1px solid black"}} >
{ this.props.proposition }
<VoteButton clickHandler={this.handleClick} label="yes" />
<VoteButton clickHandler={this.handleClick} label="no" />
</div>
);
}
}
ReactDOM.render( <VoteComponent
proposition="Want a poll?" />, document.getElementById("VOTE"));
</script>
</head>
```

Mongo

```
// CREATE
db.students.insert ({"id" :
1003675901, "name" : "Erlich
Bachmann"})
// RETRIEVE
db.students.find( { "name":
"Erlich Bachmann" }).pretty()
// find student with name Erlich
Bachmann... pretty() makes easy
to read. .count() counts Erlichs
// other operators $gt, $lt,
$eq, $gte, ...
db.students.find( { "id" : {
$gt : "100" } } ) // students
with id > 100
// OR conditions
```

Mongo (cont)

```
> db.restaurants.find(
{ $or: [ { "cuisine": "Italian" }, { "address.zipcode": "10075" } ] }
)
// sort results
db.restaurants.find().sort( { "borough": 1, "address.zipcode": 1 } ) // 1 = increasing, -1 = decreasing
// UPDATE
db.restaurants.update(
{ "restaurant_id" : "41156888" },
{ $set: { "address.street": "East 31st Street" } }
)
// DELETE
db.restaurants.remove( { "borough": "Manhattan" } ) // remove all matching criteria
db.restaurants.remove( { } ) // leaves the collection empty
db.restaurants.drop() // remove the collection
```



By **bogoSort**

cheatography.com/bogosort/

Not published yet.

Last updated 14th April, 2018.

Page 3 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>