

# Cheatography

## Cisco CLI - Security Cheat Sheet

by Mary F. Smith (boogie) via [cheatography.com/86236/cs/20725/](http://cheatography.com/86236/cs/20725/)

### Remote Access Security [ssh]

S1# **show ip ssh** verifies SSH is available and displays existing setup

S1# **configure terminal** user exec mode

S1(config)# **ip domain-name ats.coop** configures DNS

S1(config)# **crypto key generate rsa** Enables SSH and generates a RSA key pair

S1(config)# **crypto key zeroize rsa** disables SSH

Cisco will prompt you for a key name **S1.ats.coop**

Cisco will prompt you for modulus size **1024** [cisco's recommended size]

---

S1(config)# **line vty 0 15** move into vty config for all ports

S1(config-line)# **login local** allow local logins not AAA Server \*\*

### \*Cisco's Authentication Authorization & Accounting Server

S1(config-line)# **transport input ssh**

S1(config-line)# **user admin password H0u\$3M0u\$3** sets local admin login pw

S1(config)# **show ip ssh \*** verify ssh settings

Optional ssh config

- **ip ssh version 2**
- **ip ssh authentication-retries 5**
- **ip ssh time-out 60**
- **end**
- **show ip ssh**

### Show Commands

**show version**

IOS Version, Memory etc.

**show mac address-table**

Displays the MAC Address Table

**show ip route**

Displays the routing table

**show ip interface**

**show interface g0/0**

Displays the interface status, MAC, IP, etc.

**show ip interface brief**

**show running configuration**

### Port Security

### Interface Security

### Error Messages

% Invalid input detected at '^' marker	You are at the wrong level to run command
% Incomplete command	
[command brings a null response]	This is not a bad command, there is just no results to display

### Tips & Tricks

Your CLI command fails

- are you in the right mode | level
- are you on the right device

### Other Misc Commands

mydevice (config)# <b>sdm pre dual def</b>	used if switch won't take IPv6 address
?	help commands
Ctrl+Shift+6	Oh crap, stop! (Cancels whatever it's currently doing)
mydevice (config)# <b>enable secret abc123</b>	Sets secret password to abc123

## Show Commands

show ip interface brief

GigabitEthernet0/0 unassigned YES NVRAM administratively down  
down

**'Do'** - in front of a command will run the command at any level i.e.

mydevice (config)# do show ip interface brief -OR- mydevice  
(config)# do reload



By Mary F. Smith (boogie)  
[cheatography.com/boogie/](https://cheatography.com/boogie/)

Not published yet.  
Last updated 18th December, 2019.  
Page 1 of 2.

Sponsored by **Readable.com**  
Measure your website readability!  
<https://readable.com>