

Chapter 9

Angular Velocity and Acceleration

$$\Theta = \text{angle (radians)} \quad s = \text{length}$$

$$r = \text{radius} \quad 90^\circ = \pi/2 \text{ rad}$$

$$\Theta = (s/r) \quad s = r \cdot \Theta$$

$$1 \text{ rad} = (360^\circ / 2\pi) = 57.3^\circ \quad 180^\circ = \pi \text{ rad}$$

Angular Velocity (1st Derivative)

$$\omega = (\Theta_f - \Theta_i) / (t_f - t_i) \quad \omega = \text{"velocity"}$$

$$1 \text{ rev/s} = 2\pi \text{ rad/s} \quad 1 \text{ rev/min} = 1 \text{ rpm} = 2\pi/60 \text{ rad/s}$$

Angular Acceleration (2nd Derivative)

$$\alpha = (\omega_f - \omega_i) / (t_f - t_i) \quad \alpha = \text{"acceleration"}$$

Rotation w/ Constant Angular Acceleration

$$\alpha_f = (\omega_f - \omega_i) / (t - 0) \quad \alpha_f = \text{constant}$$

$$\omega_f = \omega_i + \alpha_f \cdot t$$

$$\Theta_f - \Theta_i = 1/2(\omega_i + \omega_f) \cdot t$$

$$\Theta_f = \Theta_i + (\omega_i \cdot t) + 1/2(\alpha_f \cdot t^2)$$

$$\omega_f^2 = \omega_i^2 + 2 \cdot \alpha_f(\Theta_f - \Theta_i)$$

Relating Linear and Angular Kinematics

$$K = 1/2(m \cdot v^2)$$

Linear Speed in Rigid-Body Rotation

$$s = r \cdot \Theta$$

Linear Speed

$$v = r \cdot \omega$$

Linear Acceleration in Rigid-Body Rotation

$$a_{\text{tan}} = r \cdot \alpha$$

Centripetal Component of Acceleration

$$a_{\text{rad}} = (v^2/r) = \omega^2 \cdot r$$

Energy in Rotational Motion

$$K_E: 1/2 \cdot m \cdot v^2 = 1/2 \cdot m \cdot r^2 \cdot \omega^2$$

$$K = 1/2 \cdot m \cdot r^2 \cdot \omega^2 \quad I = m \cdot r^2$$

Gravitational Potential Energy for an Extended Body

$$U = M \cdot g \cdot y_{\text{cm}}$$

Chapter 9 (cont)

Moment of Inertia

$$I_p = I_{\text{cm}} + Md^2$$

Chapter 9 Cont:

Rotational Kinetic Energy

$$K = \text{Joules}$$

$$K = 1/2 \cdot I \cdot \omega^2 \quad R = \text{Radius}$$

$$M = \text{mass pivoted about an axis}$$

Perpendicular to the Rod

$$I = (M \cdot L^2) / 3$$

Slender Rod (Axis Center)

$$I = 1/12 M \cdot L^2$$

Slender Rod (Axis End)

$$I = 1/3 M \cdot L^2$$

Rectangular Plate (Axis Center)

$$I = 1/12 M \cdot (a^2 + b^2)$$

Rectangular Plate (Axis End)

$$I = 1/3 M \cdot (a^2)$$

Hollow Cylinder

$$I = 1/2 M(R_i^2 + R_f^2)$$

Solid Cylinder

$$I = 1/2 MR^2$$

Hollow Cylinder (Thin)

$$I = MR^2$$

Solid Sphere

$$I = 2/5 MR^2$$

Hollow Sphere (Thin)

$$I = 2/3 MR^2$$

Chapter 11: Equilibrium and Elasticity

1st Condition of Equilibrium (at rest)

$$\Sigma F = 0$$

2nd Condition of Equilibrium (nonrotating)

$$\Sigma \tau = 0$$

Center of Gravity

$$r_{\text{cm}} = (m_1 \cdot r_1) / m_1$$

Solving Rigid-Body Equilibrium Problems

$$\Sigma F_x = 0$$

$$1st \text{ Condition} \quad \Sigma F_x = 0$$

$$\Sigma F_y = 0$$

$$2nd \text{ Condition (Forces xy-plane)} \quad \Sigma \tau_z = 0$$

Chapter 11: Equilibrium and Elasticity (cont)

Stress, Strain, and Elastic Moduli

Stress = Force Applied to deform a body
Strain = how much deformation

Hooke's Law

$$(\text{Stress} / \text{Strain}) = \text{Elastic Modulus}$$

$$A = \text{Area} \quad F = \text{Magnitude of Force}$$

Tensile Stress

$$F / A$$

$$1 \text{ Pascal} = 1 \text{ Pa} = 1 \text{ N/m}^2 \quad 1 \text{ psi} = 6895 \text{ Pa}$$

$$l = \text{length} \quad 1 \text{ Pa} = 1.450 \cdot 10^4$$

Tensile Strain

$$(l_f - l_i) / (l_i)$$

Young Modulus

$$(\text{Tensile Stress}) / (\text{Tensile Strain})$$

Pressure

$$p = F (\text{Force Fluid is Applied}) / A (\text{Area which force is exerted})$$

Bulk Stress

$$(p_f - p_i)$$

Bulk Strain

$$(V_f - V_i) / (V_i)$$

Bulk Modulus

$$\text{Bulk Stress} / \text{Bulk Strain}$$

Chapter 10: Dynamics of Rotational Motion

Torque

$$F = \text{Magnitude of } F \quad || || = \text{Magnitude Symbol}$$

$$\tau = F \cdot l = r \cdot F \cdot \sin \Theta = F_{\text{tan}} \cdot L \quad L = \text{lever arm of } F$$

$$\tau = ||r|| \times ||F||$$

Torque and Angular Acceleration for a Rigid Body

Newtons 2nd Law of Tangential Component

$$F_{\text{tan}} = m_1 \cdot a_1$$

Rotational analog of Newton's second law for a rigid body

$$\Sigma \tau_z = I \cdot \alpha_z \quad z = \text{rigid body about } z\text{-axis}$$



Chapter 10: Dynamics of Rotational Motion (cont)

Combined Translation and Rotation: Energy Relationships

$$K = 1/2M \cdot v^2 + 1/2I \cdot \omega^2$$

Rolling without Slipping $v = R \cdot \omega$

Combined Translation and Rotation: Dynamics

Rotational Motion about the center of mass $\Sigma \tau_z = I \cdot \alpha_z$

Work and Power in Rotational Motion $F = M \cdot a$

When it rotates from Θ_i to Θ_f $W = \int_{\Theta_i}^{\Theta_f} \tau_f d\Theta$

When the torque remains constant while angle changes $W = \tau_f (\Theta_f - \Theta_i)$

Total Work Done on rotating rigid body $W = 1/2(\omega_f^2) - 1/2(\omega_i^2)$

Power due to torque on rigid body $P = \tau_z \cdot \omega_z$

Angular Momentum $L = r \times p \text{ (} r \times m \cdot v \text{)}$

Angular Momentum of a Rigid Body $L = m_i \cdot r_i^2 \cdot \omega$

Chapter 11: Equilibrium and Elasticity (cont.)

F = Force acting tangent to the surface divided by the Area

Shear Stress F / A

h = transverse dimension [bigger] x = relative displacement (empty) [smaller]

Shear Strain x / h



By **Jaco** (brandenz1229)

cheatography.com/brandenz1229/

Published 1st December, 2021.
Last updated 1st December, 2021.
Page 2 of 2.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
<https://apollopad.com>