Cheatography

Jquery Bruce Cheat Sheet

by Bruce via cheatography.com/24245/cs/5920/

Basic Selectors

*	All Elements (including head)
#ID	Element of specified ID
.classname	Elements of classname
tagname	Elements of tagname
a[href]	Anchor with href attribute
a[href='value']	Anchor with href = 'value'
a[href|='value']	Anchor with href = 'value' **or** href starting with 'value-'
a[href^='value']	Anchor with href beginning with 'value'
a[href!='value']	Anchor with href not equal to value
a[href$='value']	Anchor with href ending with 'value'
a[href*='value']	Anchor with href containing 'value'
a[href~='value']	Anchor with href = 'value' **or** href containing complete word 'value'
a[C1][C2]	Anchor with attributes satisfying criteria C1 and C2
s1s2	Elements satisfying selector1 **and** selector2
s1,s2	Elements satisfying selector1 **or** selector2
s1>s2	Elements satisfying selector2 **and** direct child of selector1
s1 s2	Elements satisfying selector2 **and** descendants of selector1
s1+s2	Elements satisfying selector2 **and** next immediate sibiling of selector1

Basic Selectors (cont)

s1~s2	Elements satisfying selector2 **and** next sibiling of selector1

Form Filters

:button	<button> <input type = submit, reset or button>
:checkbox	
:checked	checked or selected state
:selected	selected option of <select>
:disabled	
:enabled	
:file	<input type="file">
:focus	
:image	<intput type="image">
:input	<input> <select> <textarea> <button>
:password	<input type="password">
:radio	
:reset	
:submit	
:text	<input type="text">

Attributes and Properties

$(A).attr(name)	get specified attribute value (in string) for first element in $(A)
$(A).attr(name,value|Function) $(A).attr({name:value|Function,etc}}	set specified attribute for all elements in $(A)
$(A).removeAttr(name)	
$(A).prop(name)	get specified attribute value for first element in $(A)
$(A).prop(name,value|Function) $(A).attr({name:value|Function,etc}}	
$(A).removeProp(name)	
$(A).data(name,value)	Store name=value pair in jQuery memory cache if name is my-love, it is stored as myLove

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Cheatography

Jquery Bruce Cheat Sheet

by Bruce via cheatography.com/24245/cs/5920/

Attributes and Properties (cont)

$(A).data([name])	Get name value from jQuery Cache else data-name attribute
$(A).removeData([name]) $.removeData(js element,[name])	
$.hasData(js element)	Check if element has any associated data in jqeury cache

Position Filters

:first :last :eq(n)	nth element (0-based index)
:lt(n) :gt(n)	elements before/after nth index
:even :odd	elements at even /odd index
:first-child :last-child nth-child(n) nth-child(even|odd) nth-child(Xn+Y)	n^{th} child (1-based index)
nth-last-child(n) nth-last-child(even|odd) nth-last-child(Xn+Y)	n^{th} child, starting from the last
nth-of-type(n) nth-of-type(even|odd) nth-of-type(Xn+Y)	
nth-last-of-type(n) nth-last-of-type(even|odd) nth-last-of-type(Xn+Y)	
:only-child	elements with no sibilings
:only-of-type	elements with no sibilings of same type

Content Filters

:contains(text)	elements containing text
:empty	
:has(selector)	elements containing at least one selector
:parent	elements with at least one child node

Other Filters

:animated	elements currently under animated control
:header	<h1> through <h6>
:visible	
:hidden	
:lang(language)	
:not(selector)	
:root	element which is root of the document
:target	element targeted by the document's URI's identifier

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com