

'when' methods

when(*method*, *url*, [*data*], [*headers*])

| Creates a new backend definition

whenGET(*url*, [*headers*])

| Create backend definition for GET request

whenHEAD(*url*, [*headers*])

| Create backend definition for HEAD request

whenDELETE(*url*, [*headers*])

| Create backend definition for DELETE request

whenPOST(*url*, [*data*], [*headers*])

| Create backend definition for POST request

whenPUT(*url*, [*data*], [*headers*])

| Create backend definition for PUT request

whenPATCH(*url*, [*data*], [*headers*])

| Create backend definition for PATCH request

whenJSONP(*url*)

| Create backend definition for JSONP request

Additional methods

flush(*[count]*)

| Flushes all pending requests using trained responses

resetExpectations()

| Resets all request expectations, but preserves all backend definitions. (Wipe `expect`, but keep `when`)

'expect' methods

expect(*method*, *url*, [*data*], [*headers*])

| Creates a request expectation

expectGET(*url*, [*headers*])

| Create request expectation for GET request

expectHEAD(*url*, [*headers*])

| Create request expectation for HEAD request

expectDELETE(*url*, [*headers*])

| Create request expectation for DELETE request

expectPOST(*url*, [*data*], [*headers*])

| Create request expectation for POST request

expectPUT(*url*, [*data*], [*headers*])

| Create request expectation for PUT request

expectPATCH(*url*, [*data*], [*headers*])

| Create request expectation for PATCH request

expectJSONP(*url*)

| Create request expectation for JSONP request

Additional expectations

verifyNoOutstandingExpectation()

| Verifies that all of the requests defined via the `expect` api were made.

verifyNoOutstandingRequest()

| Verifies that there are no outstanding requests that need to be flushed



By **Ryan Johnson** (CITguy)
cheatography.com/citguy/

Published 3rd March, 2015.
Last updated 11th May, 2016.
Page 1 of 1.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>