Cheatography

Meteor Cheat Sheet

by CodeChimp (codechimp) via cheatography.com/21379/cs/4100/

Command Line Tools

`meteor --help`	Prints the help information for the `meteor` command
`meteor create <ap p_n am e>`	Creates a new Application called `<ap p_n ame>`
`meteor`	Starts your application
`meteor mongo`	Connects to the running app's MongoDB instance
`meteor add <pa cka ge>`	Adds a new package to the application
`meteor reset`	Resets the project state (removes the local DB!)

Folders

`/.meteor`	Holds the meteor-specific files
`/client`	Files only visible/executed on the Client
`/clien t/c omp ati bi lity`	For JavaScript files that rely on variables declared with var at the top level. These scripts are executed without being wrapped in a new variable scope.
`/server`	Files only visible/executed on the Server
`/public`	Files servered as-is to the Client
`/private`	Files are only accessible from the Server code
`/tests`	Used for local tests only. Any files in this folder is not loaded anywhere in the running applications.

Core

`Meteor.is Client`	Value is `t rue` in client enviro- nment	*Anywhere*
`Meteor.is Server`	Value is `t rue` in server enviro- nment	*Anywhere*
`Meteor.is Cordova`	Value is `t rue` in a Cordova mobile enviro- nment	*Anywhere*
`Meteor.st artup(`*`func`*`)`	Run the function when the client/serv er starts	*Anywhere*
`Meteor.ab sol ute Url(`*`/[path], [option s]`*`)`	Generates an absolute URL pointing to the applic- ation	*Anywhere*

codechimp

By **CodeChimp** (codechimp)

cheatography.com/codechimp/

codechimp.net

Not published yet.

Last updated 12th May, 2016.

Page 1 of 1.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

https://apollopad.com