RDFa Lite Cheat Sheet

by csabaveres via cheatography.com/24809/cs/6264/

Basic Attributes

vocab	Defines the default vocabulary for a paragraph , or the whole document <body>	...
typeof	Designates the type of an individual within the current vocabulary	...
property	Provides a property in the vocabulary for the individual (property value is a text string)	Manu Sporny
property (URL)	Provides a property whose value is a URL	my homepage

Examples are adapted from the RDFa Lite 1.1 Recommendation

Intermediate Attributes

resource	Provides a handle for unique entities in the web page	...
prefix	Defines additional vocabularies	... My favorite animal is the Liger.

Examples are adapted from the RDFa Lite 1.1 Recommendation

Example using all attributes

```
<body vocab="http://schema.org/">
...
<div proper ty= " bre adc rum b">
    <a href="h ttp :// www.ib m.c om/ dev elo per wor ks/ " >IBM develo per Wor ks< /a> >
        <a href="h ttp :// www.ib m.c om/ dev elo per wor ks/ web /">Web develo pme nt< /a> >
        <a href="h ttp :// www.ib m.c om/ dev elo per wor ks/ vie ws/ web /li bra ry.j sp "
                >Te chnical librar y</ a>
</d iv>
<div typeof ="Ar tic le">
<div proper ty= " nam e">An introd uction to RDF</d iv>
<p proper ty= " aut hor " resour ce= " #uc he.o gb uji " typeof ="Pe rso n">
     by <span proper ty= " nam e">Uche Ogbuji </s pan >, <span proper ty= " job Tit le"> Par tne r</ spa -
n>,
      <span proper ty= " wor ksF or"> Zep hei ra< /sp an>.
</p>
<di v>P ubl ished: <span proper ty= " dat ePu bli she d">01 Dec 2000</ spa n>< /di v>
<div proper ty= " des cri pti on">
    <b> Sum mar y</ b>: This article introduces Resource Descri ption Framework (RDF),
    dev eloped by the W3C for Web-based metadata, using XML as an interc hange syntax.
    RDF's essential aim is to make work easier for autonomous agents,
    which would refine the Web by improving search engines and service direct ories.
    Author Uche Ogbuji gives an overview of RDF aspects from schemas to usage scenarios.
   The article assumes that you are already familiar with XML.
```

By **csabaveres**

cheatography.com/csabaveres/

Published 7th February, 2016.
Last updated 12th May, 2016.

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com

Example using all attributes (cont)

```
> </div>
<div>Tags for this article:
  <span property="keywords">introduction</span>,
  <span property="keywords">rdf</span>,
  <span property="keywords">tutorial</span>
.</div>
<div prefix="fben: http://www.freebase.com/ns/">
  This article's texts is suitable for a wide audience, with a Fog index of
  <span property="fben:gunning_fog_index">10.2</span>.
</div>
</div>
...
</body>
```

Examples are adapted from IBM developerWorks

By **csabaveres**

cheatography.com/csabaveres/

Published 7th February, 2016.
Last updated 12th May, 2016.

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com