Cheatography

PHP8 - What's New In PHP8? Cheat Sheet

by Dave Child (DaveChild) via cheatography.com/1/cs/27364/

PHP8 Variable Types

Class/interface name	An instance of the class or interface
self	The same class the type is used in
parent	The parent of the class the type is used in
callable	Something callable
bool	A boolean
int	An integer
float	A float
string	A string
array	An array
iterable	Array or traversable
object	An object
mixed	Any value
Return Types	
void	Function will not return anything
static	Function may return `static`

New mixed type

Mixed means any one of:

array	bool	callable
string	int	resource
float	null	object

Note that because `mixed` already contains `null`, it is not nullable itself.

Return static

```
class Foo
{
        public function test():
static
       {
                return new
static();
       }
}
```

Static is now a valid return type.

The nullsafe operator (copy)

```
$foo = $bar->getBaz()?-
>asFormatted();
```

Quickly check for nulls in method returns.

Union types

```
public function foo(Foo|Bar
$input): int|float;
```

You can now specify more than one type in a type hint:

- The `void` type cannot be part of a union.
- Unions can be nullable by including `null` as a type or preceding with a question mark.

Named arguments

```
function foo(string $a, int $b,
?string $c = null)
{
       ...
}
foo(
       c: 'value c',
       a: 'value a'
);
```

Pass values to functions and methods by name, regardless of the order in which they are defined.



By **Dave Child** (DaveChild)
cheatography.com/davechild/
aloneonahill.com

Published 31st March, 2021.
Last updated 31st March, 2021.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Attributes

```
use
App\Attributes\ExampleAttribute;
#[Exam ple Att ribute]
class Foo
{
        #[E xam ple Att ribute]
        public const FOO =
'foo';

        #[E xam ple Att ribute]
        public $x;

        #[E xam ple Att ribute]
        public function foo(#[ -
Exa mpl eAt tri bute] $bar) { }
}
```

Structured metadata

Match expression

```
$result = match($input) {
       0 => " hel lo",
       '1', '2', '3' => " wor -
ld",
};
```

Switch statements made simple. Note, the comparisons made by `match` use strict types.

Constructor property promotion

```
class Money
{
        public function __cons -
truct(
                public Currency
$currency,
                public int
$amount,
       ) {}
}
```

In the above example `Currency` and `int` are both automatically made public properties of the class and assigned values on construction.

Weak maps

```
class Foo
{
        private WeakMap $cache;

        public function getSom -
eth ing Wit hCa chi ng( object
$obj): object
       {
                return $this- -
>ca che [$obj]
                        ??=
$this- >co mpu teS ome thi ngE -
xpe nsi ve( $obj);
       }
}
```

A weak map allows for storage of key-value pairs, but the PHP garbage collection will drop a weak map element where the only reference to it is the weak map itself.

Throw expression

```
$triggerError = fn () => throw
new MyError();
$foo = $bar[' off set'] ?? throw
new Custom Ex( 'of fset');
```

Throw is now an expression instead of a statement, making it more flexible.

Non-capturing catches

```
try {
       // Something goes wrong
} catch (MySpe cia lEx cep tion)
{
        Log ::e rro r("S ome -
thing went wrong");
}
```

When you catch exceptions and throwables, you no longer need a variable.

::class on objects

```
$foo = new Foo();
var_du mp( $fo o:: class);
```

Works the same as `get_cl ass()`.



By **Dave Child** (DaveChild)
cheatography.com/davechild/
aloneonahill.com

Published 31st March, 2021.
Last updated 31st March, 2021.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

PHP8 - What's New In PHP8? Cheat Sheet

by Dave Child (DaveChild) via cheatography.com/1/cs/27364/

Trailing comma in parameter lists

```
public function(
        string $param eterA,
       int $param eterB,
       Foo $objec tfoo,
) {
       // …
}
```

You can now end a parameter list with a comma without an error.

Create DateTime objects from interfaces

```
DateTime::createFromInterface(DateTimeInterface
$other);
DateTi meI mmu tab le: :cr eat eFr omI nte -
rfa ce( Dat eTi meI nte rface $other);
```

New Stringable interface

```
class Foo
{
        public function __toSt -
ring(): string
       {
               return 'foo';
>   }
}
function bar(string|Stringable $stringable) { /
… / }
bar(new Foo());
bar('abc');
```

New functions

```
str_co nta ins ('h ays tack', 'needle
')
```

Does haystack contain needle?

```
str_st art s_w ith ('h ays tack', 'ne
edle')
```

Does haystack start with needle?

```
str_en ds_ wit h(' hay stack', 'needl
e')
```

Does haystack end with needle?

```
fdiv()
```

Handles division by zero without an error.

```
get_de bug _type()
```

Like gettype() but with more detail

```
get_re sou rce _id()
```

Fetch the numeric ID of a resource

Breaking Changes

Internal errors and engine warnings have been made consistent and/or reclassified.

The `@` operator no longer silences fatal errors.

The default error reporting level is now `E_ALL`.

The default PDO error mode is no longer silent.

Concatenation precedence has changed - addition now precedes concatenation.

Namespaces can now include reserved names.

`ReflectionFunction::isDisabled()` and `ReflectionParameter::isCallable()` have been deprecated.

There are more breaking and engine changes, this list is limited to those you are most likely to encounter. For a full run-down, check out Brent's article linked below.

With Thanks

This is a condensed version of the excellent PHP8 write-up you can find by Brent at stitcher.io



By **Dave Child** (DaveChild)
cheatography.com/davechild/
aloneonahill.com

Published 31st March, 2021.
Last updated 31st March, 2021.
Page 3 of 3.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com