Basic

-	open netrw file explorer
leader + w	fast saving
leader + ba	close all the buffers

Tab Management

leader + nt	open new tab
leader + tc	close actual tab
leader + tl	toggle between this and the last accessed tab
leader + tn	switch to next tab
leader + to	close other tabs
leader + tp	switch to previous tab

Telescope

;	Lists open buffers in current neovim instance
control + g	Fuzzy search through the output of git ls-files command
control + p	Lists files in your current working directory
leader + fg	Search for a string in your current working directory and get results live as you type
leader + g	Searches for the string under your cursor in your current working directory

Packer Commands

:PackerClean	Remove any disabled or unused plugins
:PackerCompile	Regenerate compiled loader file
:PackerInstall	Clean, then install missing plugins
:PackerSync	Perform PackerUpdate and then PackerCompile
:PackerUpdate	Clean, then update and install plugins

LSP Typescript Utils

leader + gi	Rename TypeScript file and update imports
leader + go	Import all missing imports in TS Files
leader + gs	Organize imports in TypeScript Files

Trouble

leader + xd	switch to document diagnostics from the builtin LSP client
leader + xr	refresh the active list
leader + xw	switch to workspace diagnostics from the builtin LSP client
leader + xx	toggle Trouble window

Git

:Git	run git command in terminal, Eg: :Git checkout -b test
leader + gR	Revert the current file to the specific commit
leader + gb	Open blame window
leader + gd	Opens a new diff that compares against the current index
leader + gn	Create a pull request with the target branch is set in the target_branch option
leader + go	Open file/folder in git repository
leader + gp	Open pull request of the current branch
leader + gr	Revert to the specific commit

Git conflict

:GitConflictListQf	Show all conflicted files in quickfix window
c0 or :GitConflictChooseNone	Select both none of the changes
cb or :GitConflictChooseBoth	Select both changes
co or :GitConflictChooseOurs	Select the current changes
ct or :GitConflictChooseTheirs	Select the incoming changes

Spectre

leader + s	open search panel
leader + sp	search in current file
leader + sw	search for selected word
When the search panel is opend we can use the following shortcuts:	
enter	goto current file
dd	toggle current item
leader + R	replace all
leader + c	input replace vim command
leader + o	show option
leader + q	send all item to quickfix
leader + rc	replace current line
leader + v	change result view mode
th	toggle search hidden
ti	toggle ignore case
tu	update change when vim write file

Sorting

leader + so	sort visual selection

Search

space	search
control + space	backward search
leader + space	remove search highlights

Split Management

control + h	Move to existing or create a new split to the left of your current window + open file or custom command
control + j	Move to existing or create a new split to the top of your current window + open file or custom command
control + k	Move to existing or create a new split to the bottom of your current window + open file or custom command
control + l	Move to existing or create a new split to the right of your current window + open file or custom command

Session Management

:SessionDelete	Delete the current session
:SessionLoad	Load the session for the current directory and current branch if git_use_branch = true
:SessionLoadLast	Load the last session
:SessionSave	Save the current session
:SessionStart	Start recording a session. Useful if autosave = false
:SessionStop	Stop recording a session
:SessionToggle	Determines whether to load, start or stop a session
leader + sm	open saved session list

LSP Installer Commands

:LspInstall [--sync] [server]	installs/reinstalls language servers. Runs in a blocking fashion if the --sync argument is passed (only recommended for scripting purposes).
:LspInstallInfo	opens a graphical overview of your language servers

LSP Installer Commands (cont)

:LspInstallLog	opens the log file in a new tab window
:LspPrintInstalled	prints all installed language servers
:LspUninstall [--sync]	uninstalls language servers. Runs in a blocking fashion if the --sync argument is passed (only recommended for scripting purposes).
:LspUninstallAll [--no-confirm]	uninstalls all language servers

LSP Commands/Shortcuts

K	Displays hover information about the symbol under the cursor in a floating window.
[+ d	Move to the previous diagnostic in the current buffer.
] + d	Move to the next diagnostic.
control + k	Displays signature information about the symbol under the cursor in a floating window
gD	Jumps to the declaration of the symbol under the cursor.
gd	Jumps to the definition of the symbol under the cursor.
gi	Lists all the implementations for the symbol under the cursor in the quickfix window.
gr	Lists all the references to the symbol under the cursor in the quickfix window.
space + ca	Selects a code action available at the current cursor position.
space + d	Jumps to the definition of the type of the symbol under the cursor.
space + e	Show diagnostics in a floating window.
space + f	Add buffer diagnostics to the location list.
space + rn	Renames all references to the symbol under the cursor.

Gitlinker

leader + gy	generate shareable file permalinks (with line ranges)

By **dcschmid**
cheatography.com/dcschmid/

Published 10th July, 2022.
Last updated 10th July, 2022.
Page 2 of 3.

Sponsored by CrosswordCheats.com
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Diffview

:DiffviewClose	generate shareable file permalinks (with line ranges)
:DiffviewFileHistory	Opens a new file history view that lists all commits that affected the given paths.
:DiffviewOpen	Open Git Diffview Tab
:DiffviewRefresh	Update stats and entries in the file list of the current Diffview

Git Worktree

leader + gw	To bring up the telescope window listing your workspaces
leader + gwn	To bring up the telescope window to create a new worktree

Comment

gb	Toggles the region using blockwise comment in visual mode
gbc	Toggles the current line using blockwise comment in normal mode
gc	Toggles the region using linewise comment in visual mode
gcc	Toggles the current line using linewise comment in normal mode