

Syntax

> Child - `nav>ul>li`

+ Sibling - `div+p+bq`

^ Climb up - `div+div>p>span+em^bq`

() Grouping - `div>(header>ul>li*2>a)+footer>p`

* Multiplication - `ul>li*5`

\$ Numbering - `ul>li.item$*5`

. Class - `h1.title or p.class1.class2.class3`

ID - `div.#header or form#search.wide`

[] Custom attributes - `td[rowspan=2 colspan=3 title]`

{ } Text - `p>{Click }+a{here}+{ to continue}`

HTML

! Create HTML5 template

a ``

a:link ``

a:mail ``

link `<link rel="stylesheet" href="" />`

meta `<meta />`

meta:utf `<meta http-equiv="Content-Type" content="text/html; charset=UTF-8" />`

style `<style></style>`

script `<script></script>`

script:src `<script src=""></script>`

img ``

form `<form action=""></form>`

form:get `<form action="" method="get"></form>`

form:post `<form action="" method="post"></form>`

label `<label for=""></label>`

inp `<input type="text" name="" id="" />`

input:ema `<input type="email" name="" id="" />`

il

HTML (cont)

input:p `<input type="password" name="" id="" />`

input:c `<input type="checkbox" name="" id="" />`

input:r `<input type="radio" name="" id="" />`

input:f `<input type="file" name="" id="" />`

select `<select name="" id=""></select>`

option `<option value=""></option>`

textarea `<textarea name="" id="" cols="30" rows="10"></textarea>`

btn:s `<button type="submit"></button>`

btn `<button></button>`

sect `<section></section>`

art `<article></article>`

hdr `<header></header>`

fttr `<footer></footer>`

mn `<main></main>`

ol+ ``

ul+ ``

dl+ `<dt></dt><dd></dd>`

table+ `<table><tr><td></td></tr></table>`

tr+ `<tr><td></td></tr>`



CSS

pos:(a|r|f) position: absolute|relative|fixed;

t top

r right

b bottom

l left

z z-index

fl:(n|r|l) float: none|right|left;

cl:(n|b|l|r) clear: none|both|left|right;

d: display:
(n|b|f|i|ib) none|block|flex|inline|inline-block;

v:(v|h) visibility: visible|hidden;

ov:(v|h|s) overflow: visible|hidden|scroll;

ovx:() overflow-x: visible|hidden|scroll;

ovy:() overflow-y: visible|hidden|scroll;

m margin

m(r|t|b|l) margin-right|top|bottom|left;

p padding

p(t|r|b|l) padding-top|right|bottom|left;

bxz:bb box-sizing: border-box;

w width

h height

maw max-width

mah max-height

miw min-width

mih min-height

fw font-weight

fz font-size

ff font-family

CSS (cont)

ta: text-align: left|center|right|justify;
(|c|r|j)

td:n text-decoration: none;

lh line-height

bg:n background: none

bg+ background: #fff url() 0 0 no-repeat;

c:(r|ra) color: rgb()|rgba();

op opacity

cnt content: '';

ol:n outline: none;

bd+ border: 1px solid #000;

bd:n border: none;

bd(t|r|b) border-top|right|left|bottom: 1px solid #000;
+

bdrs border-radius

lis:n list-style: none;

! !important

@f font-face

@kf keyframes

@m media

anim- animation

ai: align-items:

(b|c|fe|fs|s|sa|sb) baseline|center|flex-end|flex-start|stretch|space-around|space-between;

fxd:(c|r) flex-direction: column|row;



By **deftcode**

cheatography.com/deftcode/

Published 3rd June, 2017.

Last updated 3rd June, 2017.

Page 2 of 3.

Sponsored by **Readability-Score.com**

Measure your website readability!

<https://readability-score.com>

CSS (cont)

```
jc:          justify-content: baseline|flex-end|flex-  
(c|fe|fs|sa  start|space-around|space-between;  
|sb)
```

```
trf:        transform:  
(r|sc|skx|  rotate|scale|skewX|skewY|translate;  
sky|t)
```

```
trs         transition
```

```
trfo       transform-origin
```



By **deftcode**

cheatography.com/deftcode/

Published 3rd June, 2017.

Last updated 3rd June, 2017.

Page 3 of 3.

Sponsored by **Readability-Score.com**

Measure your website readability!

<https://readability-score.com>