

Modules

Define `var mod = angular.module('name', []);`
Dependency array is not an optional parameter but can be empty.

Retrieve `var mod = angular.module('name');`

Config `var mod = angular.module('name', [], function config() { });`
 - OR -
`mod.config(function config() { });`
Provider injectables only.

Run `mod.run(function run() { });`
Standard injectables only.

App Module Usage `<body ng-app="name"></body>`

[📖 Official Documentation](#)

Directives

Define `mod.directive('myDirective', function(...)`
`{`
`return {`
`restrict: 'AEC', // some combination`
`of the three`
`scope: {}, // isolate scope`
`template: 'some html',`
`templateUrl: 'path/to/template',`
`replace: true OR false,`
`transclude: true OR false,`
`require: 'directiveName',`
`link: function(scope, elem, attr,`
`controller, transcludeFn) { }`
`};`
`});`

Retrieve `mod.directive('myDirective');`

[🔗 What Everybody Ought to Know About Directive Interaction](#)

[🔗 Little Known Ways to Include Static Content in a Directive](#)

Controllers

Define `mod.controller('name', function name() { });`
Dependencies injected by named parameter.

Retrieve `var ctrl = mod.controller('name');`

Array Syntax `mod.controller('name', ['depName', function name(depName) { }]);`

Controller as Usage `<div ng-controller="name as vm"></div>`

Standard Usage `<div ng-controller="name"></div>`

[📖 Official Documentation](#)



By **[deleted]**
cheatography.com/deleted-24171/

Not published yet.
 Last updated 10th May, 2016.
 Page 1 of 1.

Sponsored by **ApolloPad.com**
 Everyone has a novel in them. Finish Yours!
<https://apollopod.com>