

Modules		Controllers	
Define	<code>var mod = angular.module('name', []);</code> Dependency array is not an optional parameter but can be empty.	Define	<code>mod.controller('name', function name() { });</code> Dependencies injected by named parameter.
Retrieve	<code>var mod = angular.module('name');</code>	Retrieve	<code>var ctrl = mod.controller('name');</code>
Config	<code>var mod = angular.module('name', [], function config() { });</code> - OR - <code>mod.config(function config() { });</code> Provider injectables only.	Array	<code>mod.controller('name', ['depName', function config() { }]);</code>
Run	<code>mod.run(function run() { });</code> Standard injectables only.	Syntax	<code>{ };</code>
App Module Usage	<code><body ng-app="name"> </body></code>	Controller as Usage	<code><div ng-controller="name as vm"> </div></code>
		Standard Usage	<code><div ng-controller="name"> </div></code>
		📖 Official Documentation	

Directives	
Define	<code>mod.directive('myDirective', function(...) { return { restrict: 'AEC', // some combination of the three scope: {}, // isolate scope template: 'some html', templateUrl: 'path/to/template', replace: true OR false, transclude: true OR false, require: 'directiveName', link: function(scope, elem, attr, controller, transcludeFn) { } }; });</code>
Retrieve	<code>mod.directive('myDirective');</code>
🔗 What Everybody Ought to Know About Directive Interaction	
🔗 Little Known Ways to Include Static Content in a Directive	



By [deleted]
cheatography.com/deleted-24171/

Not published yet.
Last updated 10th May, 2016.
Page 1 of 1.

Sponsored by [ApolloPad.com](https://apollopad.com)
Everyone has a novel in them. Finish Yours!
<https://apollopad.com>