

### 7.4.1/7.4.2 - Implement DHCPv4

#### Configure the excluded IPv4 address

```
ip dhcp excluded-address 192.168.1.0 192.168.1.10
! bzw. 192.168.30.1 192.168.30.10
```

#### Create a DHCP pool on R2 for the R1 LAN

```
ip dhcp pool R1-LAN
network 192.168.10.0 255.255.0.0
default-router 192.168.10.1
dns-server 192.168.2.0 254
```

#### Create a DHCP pool on R2 for the R3 LAN

```
ip dhcp pool R3-LAN
network 192.168.10.0 255.255.0.0
default-router 192.168.30.1
dns-server 192.168.2.0 254
```

#### Configure R1 and R3 as a DHCP relay agent

```
interface g0/0
ip helper-address 10.1.1.2 bzw. 10.2.2.2
```

#### Set PC1 and PC2 to receive IP addressing information from DHCP

#### Set PCs to DHCP

#### Configure R2 as a DHCP Client

```
interface g0/1
ip address dhcp
no shut
```

### 8.5.1 - Configure DHCPv6

#### Configure interfaces and routing for both routers

```
ip v6 local address routing
interface {interface}
ipv6 address {ipv6-address}
ipv6 address {link-local} link-local
no shutdown
ipv6 route ::/0 2001:d b8: aca d:2::2
(R1) bzw. ::/0 2001:d b8: aca d:2::1 (R2)
```

#### Configure R1 to provide stateless DHCPv6 for PC-A

```
ipv6 dhcp pool R1-STATELESS
dns-server 2001:d b8: aca d::254
domain-name STATELESS.com
interface g0/0/1
ipv6 nd other-config-flag
```

#### Configure a stateful DHCPv6 server on R1

```
ipv6 dhcp pool R2-STATEFUL
address prefix 2001:d b8: aca d:3 :aa a
::/80
dns-server 2001:d b8: aca d::254
domain-name STATEFUL.com
interface g0/0/0
ipv6 dhcp server R2-STATEFUL
```



By [deleted]  
[cheatography.com/deleted-96251/](http://cheatography.com/deleted-96251/)

Not published yet.  
 Last updated 22nd April, 2020.  
 Page 1 of 1.

Sponsored by [CrosswordCheats.com](http://CrosswordCheats.com)  
 Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>