

KEEP A CHANGELOG



Concept

Why	keepachangelog.com
What	https://pypi.python.org/pypi/gitchangelog
How	.gitchangelog.rc repository
GIT Tag	[0-9]+\.[0-9]+(\.[0-9]+)?(-.+)?(!+.)?
Tag examples	1.3.0; 1.1.2-beta1; 1.0.0-beta.3+build.20.f42cbd56
Date	(2017-08-11)
Sample result	2.1.1 (2014-04-15)

Format

ACTION: [AUDIENCE:] COMMIT_MSG [!TAG ...]

ACTION

new:	for new features, big improvement
chg:	for refactor, small improvement, cosmetic changes...
fix:	for bug fixes

AUDIENCE

dev:	for developpers (API changes, refactors...)
usr: or user:	for final users (UI changes)
pkg:	packaging changes
test:	test only related changes
doc:	doc only changes

TAG

!refactor	for refactoring code only
!minor	for a very meaningless change (a typo, adding a comment)
!cosmetic	for cosmetic driven change (re-indentation, 80-col...)
!wip	for partial functionality but complete subfunctionality

Exemples de message

new: usr:	support of bazaar implemented
chg:	re-indentend some lines !cosmetic
fix: pkg:	updated year of licence coverage.
new: test:	added a bunch of test around user usability of feature X.
fix:	typo in spelling my name in comment. !minor



By **Delqvs**
cheatography.com/delqvs/

Published 14th August, 2017.
Last updated 14th August, 2017.
Page 1 of 1.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
<https://apollopad.com>