

(Ctrl-Key)	(Ctrl-x Key)	(Meta-Key) (cont)
(C-S-?) backward-delete-char	(C-x S-) start-kbd-macro	(M-8) digit-argument
(C-S-@) set-mark	(C-x S-) end-kbd-macro	(M-9) digit-argument
(C-S-_) undo	(C-x e) call-last-kbd-macro	(M-=) possible-completions
(C-\) stty-quit		(M-\) delete-horizontal-space
(C-]) character-search	(Ctrl-x Ctrl-Key)	(M-b) backward-word
(C-a) beginning-of-line	(C-x C-S-?) backward-kill-line	(M-d) kill-word
(C-b) backward-char	(C-x C-e) edit-and-execute-command	(M-f) forward-word
(C-c) stty-intr	(C-x C-g) abort	(M-l) downcase-word
(C-d) stty-eof / delete-char	(C-x C-r) re-read-init-file	(M-n) non-incremental-forward-search-history
(C-e) end-of-line	(C-x C-u) undo	(M-p) non-incremental-reverse-search-history
(C-f) forward-char	(C-x C-v) display-shell-version	(M-t) transpose-words
(C-g) abort	(C-x C-x) exchange-point-and-mark	(M-u) upcase-word
(C-h) backward-delete-char	(C-x C-~) possible-username-completions	(M-y) yank-pop
(C-i) complete		
(C-j) accept-line	(Meta-Key)	(Meta-Ctrl-Key)
(C-k) kill-line	(M-S-#) insert-comment	(M-C-S-?) backward-kill-word
(C-l) clear-screen	(M-S-&) tilde-expand	(M-C-]) character-search-backward
(C-m) accept-line	(M-S-<) beginning-of-history	(M-C-e) shell-expand-line
(C-n) next-history	(M-S->) end-of-history	(M-C-h) backward-kill-word
(C-o) operate-and-get-next	(M-S-_) insert-last-argument	(M-C-i) dynamic-complete-history
(C-p) previous-history	(M-S-_) yank-last-arg	(M-C-r) revert-line
(C-q) stty-start / quoted-insert	(M-) set-mark	(M-C-y) yank-nth-arg
(C-r) reverse-search-history	(M-) digit-argument	
(C-s) stty-stop / forward-search-history	(M-.) insert-last-argument	Aliases
(C-t) transpose-chars	(M-.) yank-last-arg	(C-2) == (C-S-@) == (C-) and (M-) set-mark
(C-u) unix-line-discard	(M-/) complete-filename	(C-3) == (C-]) == (<ESC>) ESCAPE
(C-v) quoted-insert	(M-0) digit-argument	(C-4) == (C-\) stty-quit
(C-w) unix-word-rubout	(M-1) digit-argument	(C-5) == (C-]) character-search
(C-x) <prefix-for-more-commands>	(M-2) digit-argument	(C-6) == (C-^> <unmaped>
(C-y) yank	(M-3) digit-argument	(C-7) == (C-x C-u) == (C-_) == (C-/) undo
(C-z) stty-susp	(M-4) digit-argument	(C-8) == (C-S-?) == (<BS>) == (C-h) BACKSPACE
	(M-5) digit-argument	(C-i) == (<TAB>) TAB
	(M-6) digit-argument	(M-.) == (M-_) yank-last-argument
	(M-7) digit-argument	



Notes

(Meta-key) == (Alt-key) == (Esc-key) == (Opt-key)

🍏 For Mac users: The `Meta` key is set to the `ESC`, but you can set the `Opt` key as well. Just open the terminal and go to

Terminal > Preferences > Basic Default >

Keyboard > Use option as meta key

If you need more information, read this tutorial [more]

Didn't mapped

- () alias-expand-line
- () arrow-key-prefix
- () backward-byte
- () capitalize-word
- () copy-backward-word
- () copy-forward-word
- () copy-region-as-kill
- () dabbrev-expand
- () delete-char-or-list
- () dump-functions
- () dump-macros
- () dump-variables
- () emacs-editing-mode
- () forward-backward-delete-char
- () forward-byte
- () history-and-alias-expand-line
- () history-search-backward
- () history-search-forward
- () history-substring-search-backward
- () history-substring-search-forward
- () kill-region
- () kill-whole-line
- () magic-space
- () menu-complete
- () menu-complete-backward
- () next-screen-line
- () non-incremental-forward-search-history-again
- () non-incremental-reverse-search-history-again
- () old-menu-complete

Didn't mapped (cont)

- () overwrite-mode
- () previous-screen-line
- () print-last-kbd-macro
- () reverse-search-history
- () shell-backward-kill-word
- () shell-backward-word
- () shell-forward-word
- () shell-kill-word
- () skip-csi-sequence
- () tab-insert
- () transpose-chars
- () tty-status
- () universal-argument
- () unix-filename-rubout

