Full Bash Shortcuts Cheat Sheet

by im_Tavo (gamejia90) via cheatography.com/39342/cs/27717/

(Ctrl-Key)

(C-S-?)	backward-delete-char
(C-S-@)	set-mark
(C-S-_)	undo
(C-\)	stty-quit
(C-])	character-search
(C-a)	beginning-of-line
(C-b)	backward-char
(C-c)	stty-intr
(C-d)	stty-eof / delete-char
(C-e)	end-of-line
(C-f)	forward-char
(C-g)	abort
(C-h)	backward-delete-char
(C-i)	complete
(C-j)	accept-line
(C-k)	kill-line
(C-l)	clear-screen
(C-m)	accept-line
(C-n)	next-history
(C-o)	operate-and-get-next
(C-p)	previous-history
(C-q)	stty-start / quoted-insert
(C-r)	reverse-search-history
(C-s)	stty-stop / forward-search-history
(C-t)	transpose-chars
(C-u)	unix-line-discard
(C-v)	quoted-insert
(C-w)	unix-word-rubout
(C-x)	<prefix-for-more-commands>
(C-y)	yank
(C-z)	stty-susp

(Ctrl-x Key)

(C-x S-()	start-kbd-macro
(C-x S-))	end-kbd-macro
(C-x e)	call-last-kbd-macro

(Ctrl-x Ctrl-Key)

(C-x C-S-?)	backward-kill-line
(C-x C-e)	edit-and-execute-command
(C-x C-g)	abort
(C-x C-r)	re-read-init-file
(C-x C-u)	undo
(C-x C-v)	display-shell-version
(C-x C-x)	exchange-point-and-mark
(C-x C-~)	possible-username-completions

Aliases

(C-2) == (C-S-@) == (C-) and (M-)	set-mark
(C-3) == (C-[) == (<ESC>)	ESCAPE
(C-4) == (C-\)	stty-quit
(C-5) == (C-])	character-search
(C-6) == (C-^)	<unmaped>
(C-7) == (C-x C-u) == (C-_) == (C-/)	undo
(C-8) == (C-S-?) == (<BS>) == (C-h)	BACKSPACE
(C-i) == (<TAB>)	TAB
(M-.) == (M-_)	yank-last-argument

(Meta-Ctrl-Key)

(M-C-S-?)	backward-kill-word
(M-C-])	character-search-backward
(M-C-e)	shell-expand-line
(M-C-h)	backward-kill-word
(M-C-i)	dynamic-complete-history
(M-C-r)	revert-line
(M-C-y)	yank-nth-arg

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com

Notes

`(Meta-key) == (Alt-key) == (Esc-key) == (Opt-key)`

For Mac users: The `Meta` key is setted to the `ESC`, but you can set the `Opt` key as well. Just open the terminal and go to

Terminal > Preferences > Basic Default > Keyboard > Use option as meta key

If you need more information, read this tutorial [more]

(Meta-Key)

(M-S-#)	insert-comment
(M-S-&)	tilde-expand
(M-S-<)	beginning-of-history
(M-S->)	end-of-history
(M-S-_)	insert-last-argument
(M-S-_)	yank-last-arg
(M-)	set-mark
(M--)	digit-argument
(M-.)	insert-last-argument
(M-.)	yank-last-arg
(M-/)	complete-filename
(M-0)	digit-argument
(M-1)	digit-argument
(M-2)	digit-argument
(M-3)	digit-argument
(M-4)	digit-argument
(M-5)	digit-argument
(M-6)	digit-argument
(M-7)	digit-argument
(M-8)	digit-argument
(M-9)	digit-argument
(M-=)	possible-completions
(M-\)	delete-horizontal-space
(M-b)	backward-word
(M-d)	kill-word
(M-f)	forward-word
(M-l)	downcase-word
(M-n)	non-incremental-forward-search-history

(Meta-Key) (cont)

(M-p)	non-incremental-reverse-search-history
(M-t)	transpose-words
(M-u)	upcase-word
(M-y)	yank-pop

Didn't mapped

()	alias-expand-line
()	arrow-key-prefix
()	backward-byte
()	capitalize-word
()	copy-backward-word
()	copy-forward-word
()	copy-region-as-kill
()	dabbrev-expand
()	delete-char-or-list
()	dump-functions
()	dump-macros
()	dump-variables
()	emacs-editing-mode
()	forward-backward-delete-char
()	forward-byte
()	history-and-alias-expand-line
()	history-search-backward
()	history-search-forward
()	history-substring-search-backward
()	history-substring-search-forward
()	kill-region
()	kill-whole-line
()	magic-space
()	menu-complete
()	menu-complete-backward
()	next-screen-line
()	non-incremental-forward-search-history-again
()	non-incremental-reverse-search-history-again
()	old-menu-complete

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com

Didn't mapped (cont)	
( )	overwrite-mode
( )	previous-screen-line
( )	print-last-kbd-macro
( )	reverse-search-history
( )	shell-backward-kill-word
( )	shell-backward-word
( )	shell-forward-word
( )	shell-kill-word
( )	skip-csi-sequence
( )	tab-insert
( )	transpose-chars
( )	tty-status
( )	universal-argument
( )	unix-filename-rubout

Sponsored by **Readable.com**
Measure your website readability!
https://readable.com