

Help

<code>fossil help</code>	List help commands
<code>fossil help <command></code>	Detailed help

Create from existing data or empty checkout

`fossil new <repository>.fossil`

Change into checkout directory and open repository

```
fossil open <path/to/repository>.fossil
fossil add .
```

Clone from existing repository

Start in local repository directory

```
fossil clone http://<user>:<password>@<host>:<repository>.fossil
```

Change into checkout directory and open repository

```
cd <checkout_dir>
fossil open <path/to/repository>.fossil
```

Clone using any of

```
file://<path/to/repository>.fossil
http://<user>:<password>@<host>:<port><repository>.fossil
ssh://<user>@<host>:<port>/<path/to/repository>.fossil
```

Show

<code>fossil status</code>	Show changed files & repository details
<code>fossil extra</code>	Show unversioned files
<code>fossil change</code>	Show edit state in checkout
<code>fossil info</code>	Show basic checkout info

Adding & removing files

<code>fossil add</code>	Add one or more files to current checkout
<code>fossil rm</code>	Remove one or more files from current checkout
<code>fossil addremove</code>	Both add and remove files from next commit

Update

<code>fossil update</code>	Update checkout to latest version
<code>fossil commit -m "Commit message"</code>	Commits locally changed files and starts autosync

Synchronisation

<code>fossil sync (<url>)</code>	Sync
<code>fossil pull</code>	Pull changes from master
<code>fossil push</code>	Push local changes to master

