

### General format

General idea	PSEUDO-SQL (PQL in this context) is a formal data processing language with non-formal data definitions		
formal	In the scope of this language we speak of "formal" when the keywords and syntax is exactly defined like in a programming language or real SQL		
non-formal	In the scope of this document non-formal elements, if those elements are not, or not fully defined and are to be stated in such a way that they make sense in plain language. So we may for example reference a full-address in a statement where as in a real database this would be split into several fields		
Keywords & Syntax	The language keywords (i.e. language tokens) and syntax are formally defined. But informal statements may be introduced by the user		
Basic PQL statement	The basic PQL statement differs from the standard SQL in that the destination is usually only a name for the result of the statement. The destination and source may have the same name, stating that the source record set is to be updated. In general the result of this statement is a new destination record set which would override any existing one with same name	SELECT	destination
		FROM	source ...
Record sets	A record set is a list of records which is not formally defined. I.e. it is not mandatory that all records explicitly have the same columns available (see Missing columns).		
Initial record set(s)	Initial record sets are those which are used as source without being created by any previous PQL statement. In most cases it will not be necessary to formally introduce these as they should be informally comprehensible.		



By **Gaston**

[cheatography.com/gaston/](https://cheatography.com/gaston/)

Not published yet.

Last updated 2nd January, 2026.

Page 1 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>

### General format (cont)

Identifiers	Identifiers are names which are composed of alphanumeric character, underscore and/or minus but no space. Identifiers shall also start with a letter or underscore	
Informal columns	Column names should be informal, and thus meaning full by their name. Columns are virtual and can represent any simple or complex concept (like the employee-office-number-and-address)	
Formal columns	Sometimes informal column identifiers may get too cumbersome to describe its full usage and scope. In these cases columns may be formally defined using an informal description. The recordset name is optional in case the column is to be globally available	DEFINE [<recordset>.<column> AS <description>
	This definition simply reuses a previous column definition and may optionally alter its definition via another informal description	DEFINE <recordset>.<column> = [<recordset>.<column> BUT <description>
Missing columns	As described in the record sets topic, records in a record set are not expected to each have the same set of columns. This is handled by a set of formal rules below	
	RULE 1: tests	Missing columns being assumed empty they behave like empty columns in any test
	RULE 2: assignment	Any value assigned to a non-existent column virtually creates that column in the given record. This rule generally allows to add new columns to any recordset
WHERE condition	Just like in plain SQL, PSQ allows to filter records via the WHERE keyword. The conditions are PQL specific however	



By **Gaston**

[cheatography.com/gaston/](https://cheatography.com/gaston/)

Not published yet.

Last updated 2nd January, 2026.

Page 2 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>

### General format (cont)

**JOINS** Joins being pure SQL database technical statments, they are not used in PQL. If at any time select data from several record sets are required as source, a record set should be previously created by a PQL statement making it easier comprehensible

### Conditions

'condi- Informal conditions are to be written in single quotes.  
tion' or Additional parenthesis may be added for better readab-  
( 'cond- ility where required  
ition' )

NOT | Boolean operators in order of precedence (highest to  
AND | lowest)  
OR

( Conditions can be grouped in parentheses to manage  
condition proper precedence  
)



By **Gaston**

[cheatography.com/gaston/](https://cheatography.com/gaston/)

Not published yet.

Last updated 2nd January, 2026.

Page 4 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>

