Cheatography

Algoritmica Cheat Sheet

by greatcraic via cheatography.com/21020/cs/3866/

Algoritmi di ordinamento

ALGORITMO	Tempo	Spazio
Selection Sort	$\Theta(n^2)$	sul posto $\Theta(1)$
Insertion Sort *	Ottimo: Θ (n) Medio: $\Theta(n^2)$ Pessimo $\Theta(n^2)$	sul posto $\Theta(1)$
MergeSort *	Θ (n log n)	Θ(n)
QuickSort	Ottimo Θ(nlogn) Medio: Θ(nlogn) Pessimo: $\Theta(n^2)$	sul posto $\Theta(1)$ (ma spazio non costante x ricorsione)
HeapSort	Θ (n log n)	sul posto $\Theta(1)$
CountingSort *	Θ (n + k)	
RadixSort *	Θ (d(n+k))	

SelectionSort

```
for i =1 to n-1 {
      minimo = i;
   for j=i+1 to n {
          if (a[j] < a[minimo])
minimo = j;
     }
      scambia a[j] e a[minimo];
}
```

Insertion Sort

```
for j = 2 to n {
     key = a[j];
     i = j - 1;
   while (i > 0 && a[i] > key)
{
              a[i+1] = a[i];
             i--;
     }
a[i+1] = key;
}
```

MergeSort

```
MergeSort(a, sx, dx)
if (sx < dx) {
     cx = (sx+dx)/2; //parte
intera inferiore
   MergeSort(a, sx, cx);
   MergeSort(a, cx+1, dx);
   Merge(a, sx, cx, dx);
}
Merge(a, sx, cx, dx)
n1 = cx - sx + 1;
n2 = dx - cx;
L = nuovo array di dim n1+1
R = nuovo array di dim n2+1
for(i = 1; i ≤ n1; i++) L[i] =
a[sx+i-1];
for(j = 1; j ≤ n1; j++) R[j] =
a[cx+j];
L[n1+1] = ∞ //sent inella
R[n2+1] = ∞ //sent inella
i = 1;
j = 1;
for(k=sx; k ≤ dx; k++) {
   if (L[i] ≤ r[j]) {a[k] =
L[i]; i++;}
   else {a[k] = R[j]; j++}
]
```

QuickSort

```
QuickSort(A, p, r)
if (p < r) {
     q = partit ion(A, p, r);
      Qui ckS ort(A, p, q-1);
      Qui ckS ort(A, q+1, r);
}
Partition(A, p, r) {
//nella versione random generare
i = numero //random tra p e r
//e metterlo in fondo
     x = A[r];
     i = p-1;
   for j = p to r -1 {
      if(a[j] ≤ x) {
                i++;
                 scambia A[i]
con A[j];
           }
     }
scambi a(A [i+1], A[r]);
return i+1;
```

Heap

```
Max-Heapify(A, i)
   l = Left(i);
   r = Right(i);
  if l ≤ A.heapsize and A[l] >
A[i]
        massimo = l;
  else massimo = i;
  if r ≤ A.heapsize and A[r] >
A[massimo]
        massimo = r;
  if massimo ≠ i
        scambia A[i] con
A[mass imo];
        Max -He api fy(A,
massimo);
Build- Max -Heap
    A.h eapsize = A.length;
  for i = A.length/2 downto 1
```



By **greatcraic**

cheatography.com/greatcraic/

Not published yet.

Last updated 12th May, 2016.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

https://apollopad.com

Heap (cont)

```
>    Max-Heapify(A, i);
Heapsort(A)
 Build-Max-Heap(A);
 for i = A.length downto 2
  scambia A[1] con A[i]
  A.heapsize--;
  Max-Heapify(A, 1);
```

Code di priorità

```
Heap-Maximum(A) return A[1];
Heap-E xtr act -Max(A)
  if A.heap -size < 1
    error " und erflow dell'h -
eap "
   max = A[1];
   A[1] = A[A.he apsize]
    A.h eap size--;
    Max -He api fy(A, 1);
  return max;
Heap-I ncr eas e-Key (A, i, key)
  if key < A[i]
    error "la nuova chiave è
più piccola di
                      quella
corren te";
   A[i] = key;
  while i > 1 and A[Pare nt( -
i)]  < A[i]
        scambia A[i] con
A[Pare nt(i)];
       i = Parent(i);
Max-He ap- Ins ert(A, key)
    A.h eap size++;
    A[A.he apsize] = -∞;
    Hea p-I ncr eas e-key (A,
A.heap size, key)
```

CountingSort

```
CountingSort (A, k)
C[0..k] nuovo array di
dimensione k
//nota che qui conto da 0
for i = 0 to k
```

CountingSort (cont)

```
>  C[i] = 0;
for i = 0 to n
  C[A[i]]++;
for i = 1 to k
  C[i] = C[i-1] + C[i];
for i = n downto 1 {
  B[C[A[i]]] = A[i];
  C[A[i]]--;
}
```

RadixSort

```
RadixSort(A, d)
for i = 1 to d
     usa un ordina mento stabile
per ordinare
      l'array A sulla cifra i
```

Ricerca Binaria (tempo log n)

```
RicercaBinaria(a, sx, dx, k)
  if (sx > dx) return -1;
   cx = sx + dx / 2;
  if (a[cx] == k) return cx;
  if (a[cx] > k)
        return Ricerc aBi nar -
ia(a, sx, cx-1, k);
  else
        return Ricerc aBi nar -
ia(a, cx+1, dx, k);
Ricerc aBi nar iaSx(a, sx, dx,
k)
  if (sx > dx) return -1;
  if (sx == dx) {
    if (a[sx] == k) return sx;
    else return -1;
   }
   cx = sx + dx / 2;
  if (a[cx] ≥ k)
        return Ricerc aBi nar -
ia(a, sx, cx, k);
  else
        return Ricerc aBi nar -
ia(a, cx+1, dx, k);
```

Randomized-Select (QuickSelect)

```
//Trova la i-esima occorrenza +
piccola in //tempo atteso
lineare
Random ize d-S ele ct(A, p, r,
i)
  if (p == r)
        return A[p];
   q = Random ize d-P art iti -
on(A, p, r); //vedi
                                -
                                -
          //q uic ksort
   k = q - p + 1;
  if (i == k) // il valore del
pivot è la
                          //
soluzione
     return A[q];
  else if (i < k)
    return Random ize d-S ele -
ct(a, p, q-1, i)
  else
    return Random ize d-S ele -
ct(a, q+1, r, i-k)
```



By **greatcraic**
cheatography.com/greatcraic/

Not published yet.
Last updated 12th May, 2016.
Page 2 of 2.

Sponsored by **ApolloPad.com**
Everyone has a novel in them. Finish Yours!
https://apollopad.com