

### Tennu Subscriber Method .on() Parameters

message	handler
!command	handler
message1 message2	handler
{message1: handler1, message2: handler2}	

### Tennu Message Properties

ALL	receiver	Client
ALL	prefix	string
ALL	command	string
ALL	params	[string]
ALL	tags	object?
MOST	hostname	{nickname, username, hostname}
MOST	nickname	string
MOST	channel	string
PRIVMSG, NOTICE	isQuery	boolean
PRIVMSG, NOTICE	message	string
QUIT, JOIN	reason	string

### Tennu Output Methods

say	message
act	action
ctcp	request[, ...args]
join	channel(s)
part	channel[, reason]
quit	[reason]
nick	new-nick
mode	target, plus, minus, inArgs
who	channel
whois	nickname
userhost	nickname
raw	params...
rawf	format, params...

joining a single channel or whoising a single user returns a Promise<Result<Info, FailMessage>, Error>.

### Tennu Client Logger Methods

log	(level, ...messages)
debug	(...messages)
info	(...messages)
notice	(...messages)
warn	(...messages)
error	(...messages)
crit	(...messages)
alert	(...messages)
emerg	(...messages)



By **Havvy**  
[cheatography.com/havvy/](https://cheatography.com/havvy/)

Published 31st December, 2013.  
 Last updated 15th February, 2015.  
 Page 1 of 1.

Sponsored by **Readability-Score.com**  
 Measure your website readability!  
<https://readability-score.com>