

# WJEC A2 Computing Unit 3.1->3.3 Cheat Sheet by AlexHoratio (Horatio) via cheatography.com/21127/cs/16024/

### Records

Made up of multiple fields

Each field consists of a single data type

Each record is processed as a single item

### **Binary Trees**

Binary trees are tree entities wherein each element has no more than two children.

### Pre-Order Traversal

- 1. Root
- 2. Left
- 3. Right

### In-Order Traversal

- 1. Left
- 2. Root
- 3. Right

### Post-Order Traversal

- 1. Left
- 2. Right
- 3. Root

## De Morgan's Law

De Morgan's law states that NOT(A OR B) is the same as NOT(A) AND NOT(B).

Also, NOT(A AND B) is the same as NOT(A) OR NOT(B).

### Recursion

A recursive function is a function that calls itself repeatedly until a certain condition is met, at which point it "collapses" and returns a result.

## Data Validatio

Presence	This check ensures that
Check	something has been entered.
Range	Ensures that data is within a
Check	given range.
Туре	Checks to make sure the data
Check	is of the correct type(i.e Integer,
	String, Float)

## Data Validatio (cont)

i Ullilat	Liisules that the data follows a
Check	particular format (for use with
	Post Codes)
List	Ensures that data is one of a
Check	given list of options, for example
	"M", "F" or "X" for a gender check
Length	Make sure that the data is of the
Check	correct length(in terms of charac-
	ters, digits or elements)

Ensures that the data follows a

## Dijkstra's Pathfinding Algorithm

- 1. Start from the first vertex, named A.
- 2. Work out the weight from the A to each other connected node, in this case B and C. Add these costs to a list and order the list from lowest cost to highest.
- 3. "Move" to the node that has the lowest cost in the list.
- 4. Calculate the cost to move from A to any nodes adjacent to the currently visited node, and add these costs to the list.
- 5. Ignore longer routes(for instance, going from A to B to C rather than A to C)
- 6. Repeat steps 2->5 until you arrive at your destination.

Stacks are LIFO(Last In, First Out), so items can be pushed or popped from the top of the stack

Stacks may be used for:

- 1. Storing return addresses
- 2. Storing intermediate steps in arithmetic operations
- 3. Interrupts

A hash table is composed of both a table of data and a key. The key is a smaller file which identifies the location of a specific piece of data in the much larger table.

A hashing calculation is performed on each piece of data before it is placed into the table. The location it is placed at is determined via the result of the hash.

If there is a hash collision, one of two things will happen:

- 1. Chaining This is where a list is created in the memory location where a collision has occurred and each element that is stored there becomes an element in that list.
- 2. Rehashing This involves running another hashing algorithm on the result of the first hash to obtain a new memory location.

### **Data Verification**

Digit

Screen	This is a visual check to ensure
Verifi-	that no errors have been made.
cation	For instance, sending the data
	back to the source to check ove
	it.
Double	This is where data is entered

Dou twice to confirm i.e passwords or e-mail addresses. Keying Check This can be used for numerical

> data like credit card numbers or ISBNs, where one digit is the result of a mathematic calculation performed on the others.



By AlexHoratio (Horatio)

cheatography.com/horatio/

Published 7th June, 2018. Last updated 7th June, 2018. Page 1 of 2.

Sponsored by CrosswordCheats.com Learn to solve cryptic crosswords! http://crosswordcheats.com

alexhoratiogamedev.blogspot.com



# WJEC A2 Computing Unit 3.1->3.3 Cheat Sheet by AlexHoratio (Horatio) via cheatography.com/21127/cs/16024/

# Lossy Compression

Some of the data is "lost" during compre-

Lossy data types include JPEG, MPEG or MP3

Queues are FIFO(First In, First Out).

These would be used for

- 1. Holding tasks for the computer to run
- 2. A keypress buffer
- 3. Spooling output to a disk while waiting for a printer

## Graphs

Graphs can relate any number of element to any other number of elements.

A Weighted Graph is where there is a value on each edge which represents the "cost" of traversing it.

Graphs can either be directed or undirected.

- 1. A directed graph is a graph wherein there is a one-way relationship between each node.
- 2. An undirected graph is a graph wherein the relationship is bidirectional between each node.

# Data Flow Diagrams

What it looks like	What it is
Weird Double- Square Lookin Thing	External Entity
Rounded Square	Process
Rectangle Missing the Right Edge	Data Storage
Arrow	Represents the flow of data(should be labelled)

By AlexHoratio (Horatio)

cheatography.com/horatio/

# Big-O Notation

Constant	No matter how much data you
Time	give this algorithm, it will
O(1)	always execute in the same
	amount of time.
Linear	The time taken for the
Time	algorithm to run is directly
O(n)	proportional to the size of the
	input data.

Polynomial Time  $O(n^2)$ 

The time taken increases proportional to the square(or cube, or any other power greater than one) of the input

Exponential Time  $O(2^n)$ 

The time taken will double with every additional unit(or triple, etc- the 2 can be any number greater than one) of input data.

Logarithmic Time O(Log(n))

The time taken increases logarithmically, so the rate of increasing time with respect to input size actually decreases.

# Lossless Compression

No data is lost in the process, and the entire original file can be reconstructed.

Another type of lossless compression is via Dictionary Encoding, where the most frequent elements of data are removed and instead replaced with a "token" that points to the piece of data somewhere else in the file to prevent needless data duplication.

Also in **Huffman Coding**, the most frequent elements of data are given the shortest token to maximize compression.

One type of lossless compression is known as Run Length Encoding, where strings of the same data(e.g, "BBBBBBBB") are replaced with the number of times to place the data in a row when decompressing it. (8B)

Published 7th June, 2018. Last updated 7th June, 2018. Page 2 of 2.

Sponsored by CrosswordCheats.com Learn to solve cryptic crosswords! http://crosswordcheats.com



alexhoratiogamedev.blogspot.com