

Get Started

Install Flutter	https://flutter.dev/docs/get-started/install
Install Android Studio	https://flutter.dev/docs/get-started/editor?tab=androidstudio
Install Flutter plugin in Android Studio	File -> Settings -> Plugins -> Flutter
Iphone as Mobile Device	Buy Developer Account or use Emulator
Other Mobile Device	Connect using by USB and enable Developer Mode
Emulator	AVD Manager -> Create Virtual Device
Hot Reload	STRG+S -> App is updated automatically

Subclass State

```
class _FavoriteWidgetState extends
State<FavoriteWidget> {
  // ...
  @override
  Widget build(BuildContext context) {
    return Row(
      mainAxisAlignment: MainAxisAlignment.min,
      children: [
        Container(
          padding: EdgeInsets.all(0),
          child: IconButton(
            icon: (_isFavorited ? Icon(Icons.star)
: Icon(Icons.star_border)),
            color: Colors.red[500],
            onPressed: _toggleFavorite,
          ),
        ),
        SizedBox(
          width: 18,
          child: Container(
            child: Text('${_favoriteCount}'),
          ),
        ),
      ],
    );
  }
}
```

Parent widget

```
class ParentWidget extends StatefulWidget {
  @override
  _ParentWidgetState createState() => _ParentWi-
dgetState();
}
class _ParentWidgetState extends State<ParentWi-
dget> {
  bool _active = false;
  void _handleTapboxChanged(bool newValue) {
    setState(() {
      _active = newValue;
    });
  }
  @override
  Widget build(BuildContext context) {
    return Container(
      child: TapboxC(
        active: _active,
        onChanged: _handleTapboxChanged,
      ),
    );
  }
}
```

Displaying a full-screen route

```
Navigator.push(context, MaterialPageRoute<void>(
  builder: (BuildContext context) {
    return Scaffold(
      appBar: AppBar(title: Text('My Page')),
      body: Center(
        child: FlatButton(
          child: Text('POP'),
          onPressed: () {
            Navigator.pop(context);
          },
        ),
      ),
    );
  },
));
Navigator.pop(context);
```

Custom Route

```
Navigator.push(context, MaterialPageRoute(  
  opaque: false,  
  pageBuilder: (BuildContext context, __, ___) {  
    return Center(child: Text('My PageRoute'));  
  },
```

C

By **huemac16**

cheatography.com/huemac16/

Not published yet.

Last updated 23rd March, 2020.

Page 2 of 2.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>