Cheatography

Network Concepts Cheat Sheet by jask_skull (jask_skull) via cheatography.com/147635/cs/32110/

OSI Layers	
Applic- ation Layer	Includes all the services of a user application, including the interaction with the end user. Protocols: FTP, HTTP, SMTP Devices: Hosts, Servers
Presen- tation Layer	Provides services to the application layer to deal with specific syntax, which is how data is presented to the end user
Session Layer	Provides services to the presentation layer to establish a session and exchange presentation layer data
Transport Layer	Includes services for end-to-end connection establ- ishment and information delivery. Protocols: TCP, UDP Devices: Stateful firewalls
Network Layer	Includes the function necessary to transmit information across a network and provides abstraction on the underlying means of connection. Protocol: IP Devices: Router
Data Link Layer	Includes protocols and functions to transmit information over a link between two connected devices. Protocols: Ethernet, PPP, ATM Devices: Switches
Physical Layer	Provides services for the transmission of bits over the data link. Protocols: Ethernet, cable, optical Devices: Repeater

Encapsulation

L7 - Application	Data L7 H	L7 PDU
L6 - Presentation	L6SDU L6 H	L6 PDU
L5 - Session	L5SDU L5 H	L5 PDU
L4 - Transport	L4SDU L4 H	L4 PDU
L3 - Network	L3SDU L3 H	L3 PDU
L2 - Data Link	L1 T L2SDU L2 H	L2 PDU
L1 - Physical	11101010001100010010101010100100100101111	

Encapsulation: Each layer protocol adds its own protocol header and passes the information to the lower-layer protocol

Protocol Control Information (PCI): Is the information added by the protocol

Protocol Data Unit (PDU): Is composed by the data produced at that layer plus the PCI for that layer

Service Data Unit (SDU): A unit of data that has been passed down from a layer or sublayer to a lower layer



By jask_skull (jask_skull) cheatography.com/jask-skull/

Not published yet. Last updated 16th May, 2022. Page 1 of 3.

Ethernet Physical Layer

10BASE-T	IEEE standard: 802.3 (Ethernet) Speed: 10 Mbps Media: Twisted pair (copper) Maximum Distance: 100 m	
100BASE-T	IEEE standard: 802.3u (FastEthernet) Speed: 100 Mbps Media: Twisted pair (copper) Maximum Distance: 100 m	
1000BASE-T	IEEE standard: 802.3ab (GigaEthernet) Speed: 1000 Mbps Media: Twisted pair (copper) Maximum Distance: 100 m	
1000BASE-LX	IEEE standard: 802.3z (GigaEthernet) Speed: 1000 Mbps Media: Long wavelength (single-mode fiber) Maximum Distance: 5 km	
10GBASE-T	IEEE standard: 802.3an (10 GigaEthernet) Speed: 10 Gbps Media: Twisted pair (copper) Maximum Distance: 100 m	
Each standard name follows the format sTYPE-M s: The speed. For example, 1000 TYPE: The modulation type. For example, baseband [BASE] M: The information about the medium. Examples include T for		

twisted pair, F for fiber, L for long wavelength, and X for external sourced coding

Ethernet Medium Access Control

Half	Two Ethernet devices share a common transmission
duplex	medium. The access is controlled by implementing Carrier
	Sense Multiple Access with Collision Detection (CSMA/CD) $$
Full	Two devices can transmit simultaneously because there is
duplex	a dedicated channel allocated for the transmission.
	Because of that, there is no need to detect collisions or to
	wait before transmitting

Sponsored by Readable.com Measure your website readability! https://readable.com

Cheatography

Network Concepts Cheat Sheet by jask_skull (jask_skull) via cheatography.com/147635/cs/32110/



Carrier Sense Multiple Access/Collision Detection:

When a collision occurs, it is detected by CSMA/CD-enabled devices, which will then stop transmitting and will delay the transmission for a certain amount of time, called the backoff time. The jam signal is used by the station to signal that a collision occurred. All stations that can sense a collision are said to be in the same collision domain

Ethernet Frame		
Preamble	Length in Bytes: 7 Function: Used for the two stations for synchronization purposes	
Start Frame Delimeter	Length in Bytes: 1 Function: Indicates the start of the Ethernet frame. This is always set to 10101011	
Destin- ation Address	Length in Bytes: 6 Function: Contains the recipient address of the frame	
Source Address	Length in Bytes: 6 Function: Contains the source of the frame	
Length/T ype	Length in Bytes: 2 Function: This field can contain either the length of the MAC Client Data (length interpretation) or the type code of the Layer 3 protocol transported in the frame payload (type interpretation)	

Ethernet Frame (cont) MAC Length in Bytes: 46-1500 Client Function: This field contains information being encaps-Data and ulated at the Ethernet layer. The minimum length is 46 bytes and the maximum length depends on the type of Pad Ethernet frame: - 1500 bytes for basic frames - 1504 bytes for Q-tagged frames - 1982 bytes for envelope frames Length in Bytes: 4 Frame Check Function: This field is used by the receiving device to Sequence detect errors in transmission Ethernet Addresses Broadcast A broadcast MAC address is obtained by setting all 1s in the MAC address field. This results in an address like FFFF.FFFF. A frame with a broadcast destination address is transmitted to all devices within a LAN Multicast A frame with a multicast destination MAC address is transmitted to all frames belonging to the specific group Unicast A unicast address is associated with a particular device's NIC or port. It is composed of two sections. The first 24 bits contain the Organizational Unique Identifier (OUI) assigned to an organization. The other portion of the MAC address can be assigned by the vendor itself To transmit a frame, Ethernet uses source and destination addresses. The Ethernet addresses are called MAC addresses, or Extended Unique Identifier (EUI), and they are either 48 bits or 64 bits. The MAC address is usually expressed in hexadecimal. The following two ways are the ones used the most: 01-23-45-67-89-ab (IEEE 802 notation)

0123.4567.89ab (Cisco notation)

С

By jask_skull (jask_skull) cheatography.com/jask-skull/

Not published yet. Last updated 16th May, 2022. Page 2 of 3. Sponsored by Readable.com Measure your website readability! https://readable.com

Cheatography

LAN Switches



Collision Domain: Two or more stations needing to share the same medium.

LAN Switch: Device that allows multiple stations to connect in full-duplex mode. This creates a separate collision domain for each of the ports.

Switch Frame Fowarding

MAC address table	This table holds the link between a MAC address and the physical port of the switch where frames for that MAC address should be forwarded
Dynamic MAC address learning	This mechanism helps populating the MAC address table. When a switch receives an Ethernet frame on a port, it notes the source MAC address and inserts an entry in the MAC address table, marking that MAC address as reachable from that port
Ethernet Broadcast domain	A broadcast domain is formed by all devices connected to the same LAN switches. Broadcast domains are separated by network layer devices such as routers. An Ethernet broadcast domain is sometimes also called a subnet

By jask_skull (jask_skull)

cheatography.com/jask-skull/

Not published yet. Last updated 16th May, 2022. Page 3 of 3. Sponsored by Readable.com Measure your website readability! https://readable.com