

### Anchors

^	Start of line
\$	End of line

### Character Classes

\s	White space character
\S	Non-white space character
\d	Digit character
\D	Non-digit character
\w	Word
\W	Non-word (e.g. punctuation, spaces)

### Metacharacters (must be escaped)

^	[	]
\$	(	)
.	{	}
*	+	?
\		-

### GA Filter group accessors

\$Ax	Access group x in field A (e.g. \$A1)
\$Bx	Access group x in field B (e.g. \$B1)

### Quantifiers

*	Zero or more (greedy)
*?	Zero or more (lazy)
+	One or more (greedy)
+	One or more (lazy)
?	Zero or one (greedy)
??	Zero or one (lazy)
{X}	Exactly X (e.g. 3)
{X,}	X or more, (e.g. 3)
{X, Y}	Between X and Y (e.g. 3 and 5)
{X, Y}	(lazy)

### Ranges and Groups

.	Any character
(a b)	a or b (case sensitive)
(...)	Group, e.g. (keyword)
(?:...)	Passive group, e.g. (?:keyword)
[abc]	Range (a or b or c)
[^abc]	Negative range (not a or b or c)
[A-Z]	Uppercase letter between A and Z
[a-z]	Lowercase letter between a and z
[0-7]	Digit between 0 and 7

### Sample Patterns

**^/directory/(.\*)**  
*Any page URLs starting with /directory/*

**(brand\s\*?term)**  
*Brand term with or without whitespace between words*

**^brand\s+[^cf]**  
*Key phrases beginning with 'brand' and the second word not starting with c or f*

**\.aspx\$**  
*URLs ending in '.aspx'*

**ORDER\d{6}**  
*"ORDER-" followed by a six digit ID*

**(?:\?|&)utm=([^\&\$]+)**  
*Value of 'utm' querystring parameter*



By **Jay Taylor** (Jay Taylor)  
[cheatography.com/jay-taylor/](http://cheatography.com/jay-taylor/)  
[www.littledata.io](http://www.littledata.io)

Published 10th February, 2012.  
 Last updated 12th May, 2016.  
 Page 1 of 1.

Sponsored by **Readable.com**  
 Measure your website readability!  
<https://readable.com>