## Directory Operation

| | | |
|---|---|---|
| md or mkdir | `md folder _name` | Creates a directory |
| del | `del file_name` | Delete files in subdirectory |
| rd or rmdir | `rd folder _name` | Delete folder |
| rd or rmdir | `rd /s folder _name` | Delete not empty folder |
| rename or ren | `ren old_name new_name` | rename files |
| dir | `dir a*` | Display folders or files start with **a** |
| TREE | `tree` | Graphically display directory structure |
| COPY | `copy src_file des_file` | copy file |
| XCOPY | `xcopy src_file des_file /e /i` | copy folder include empty folder |
| Copy con | `copy con filena me.txt` | create file and edit |

`del /s` : delete specific file from all subdirectories

`rd /s` : delete a folder and everything in it

`tree /f` : display include file

`xcopy src_file des_file /e /i` : /e is for copy even empty folder

`xcopy src_file des_file /s /i` : /s is for copy only not empty folder

## System

| | | |
|---|---|---|
| VER | `ver` | display windows version |
| TIME | `time` | display and change time |
| DATE | `date` | display and change date |

## About

I will add more.

By **JettCalder**
cheatography.com/jettcalder/

Not published yet.
Last updated 21st February, 2017.
Page 1 of 1.