

### Common Options of Proutil

|                     |                                                                                                                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bigrow              | Format a specified number of BI Clusters in one operation.<br>Example: proutil dbname -C bigrow <# of clusters desired minus 4>                                                                                                                      |
| busy                | Determines if a database is in use by another OpenEdge process.                                                                                                                                                                                      |
| Conv10-11/con-v1112 | Convert a version 10 database to version 11, or version 11 to version 12.                                                                                                                                                                            |
| dbanalys            | Do a complete analysis of database population and fragmentation for data and indexes. This option is covered in detail in the Performance Tuning chapter. An optional Area name can be specified.<br>Example: proutil dbname -C dbanalys <area name> |
| dbipcs              | Display shared memory information for all database Brokers on a Unix system. Not supported on Windows.<br>Example: proutil -C dbipcs                                                                                                                 |

### cont...

|          |                                                                                                                                                     |
|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| holder   | Determine the mode of operation for a database                                                                                                      |
| idxbuild | Rebuild and activate one or more indexes. Offline only.                                                                                             |
| idxcheck | Report index corruption                                                                                                                             |
| idxfix   | Rebuild one or more indexes, or keys. Can be run online or offline. Checks that all keys point to records and that all records have the proper keys |

### cont... (cont)

|                          |                                                                                                                                                             |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| increaseto               | Increase selected Broker startup parameters (-B, -L, -aibufs, -bibufs, -Mxs) online (new options appearing in new releases). There is no "reduceto" option. |
| disablesi-terepl-ication | Disable OpenEdge Replication                                                                                                                                |
| dump/dumpsp-ecified      | Binary data dump                                                                                                                                            |
| enablelar-gefiles        | Allow database files to exceed the 2gb limit (default in v12)                                                                                               |
| enablesit-erepli-cation  | Enable OpenEdge Replication                                                                                                                                 |

### cont...

|                     |                                                                                                                                                    |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| indexmove / idxmove | Move an index from one Area to another                                                                                                             |
| iostats             | Report miscellaneous I/O statistics for a database                                                                                                 |
| load                | Binary data load.                                                                                                                                  |
| mvschema            | Separate data from the schema into separate Storage Areas                                                                                          |
| tabanalys           | Displays space and fragmentation information for all tables in a database. A subset of the dbanalys option. An optional Area name can be specified |
| tablemove           | Move a table from one Area to another                                                                                                              |

### cont... (cont)

|                           |                                                                                                                                                                                                                                                                                                      |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| truncate bi               | Go through crash recovery and then truncate all BI Clusters. Optionally set the BI Cluster size with the -bi option (in 1k units). Optionally set the BI Block size with the -biblocksize option (in 1k units).<br>Example: proutil db -C truncate bi [-bi <cluster size> -biblocksize <block size>] |
| update-schema / updatevst | Update the Metaschema or VST schema for new versions of OpenEdge                                                                                                                                                                                                                                     |



By **jobbygeorge**

[cheatography.com/jobbygeorge/](https://cheatography.com/jobbygeorge/)

Not published yet.

Last updated 14th May, 2023.

Page 1 of 1.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

<https://apollopad.com>