

Common Options of Proutil

bigrow Format a specified number of BI Clusters in one operation.
Example: proutil dbname -C bigrow <# of clusters desired minus 4>

busy Determines if a database is in use by another OpenEdge process.

Conv10-11/con-v1112 Convert a version 10 database to version 11, or version 11 to version 12.

dbanalys Do a complete analysis of database population and fragmentation for data and indexes. This option is covered in detail in the Performance Tuning chapter. An optional Area name can be specified.
Example: proutil dbname -C dbanalys <area name>

dbipcs Display shared memory information for all database Brokers on a Unix system. Not supported on Windows.
Example: proutil -C dbipcs

cont...

holder Determine the mode of operation for a database

idxbuild Rebuild and activate one or more indexes. Offline only.

idxcheck Report index corruption

idxfix Rebuild one or more indexes, or keys. Can be run online or offline. Checks that all keys point to records and that all records have the proper keys

cont... (cont)

increaseto Increase selected Broker startup parameters (-B, -L, -aibufs, -bibufs, -Mxs) online (new options appearing in new releases). There is no "reduceto" option.

disablesi-terepl-ication Disable OpenEdge Replication

dump/dumpsp-ecified Binary data dump

enablelar-gefiles Allow database files to exceed the 2gb limit (default in v12)

enablesit-erepli-cation Enable OpenEdge Replication

cont...

indexmove / idxmove Move an index from one Area to another

iostats Report miscellaneous I/O statistics for a database

load Binary data load.

mvschema Separate data from the schema into separate Storage Areas

tabanalys Displays space and fragmentation information for all tables in a database. A subset of the dbanalys option. An optional Area name can be specified

tablemove Move a table from one Area to another

cont... (cont)

truncate bi Go through crash recovery and then truncate all BI Clusters. Optionally set the BI Cluster size with the -bi option (in 1k units). Optionally set the BI Block size with the -biblocksize option (in 1k units).
Example: proutil db -C truncate bi [-bi <cluster size> -biblocksize <block size>]

update-schema / updatevst Update the Metaschema or VST schema for new versions of OpenEdge



By **jobbygeorge**

cheatography.com/jobbygeorge/

Not published yet.

Last updated 14th May, 2023.

Page 1 of 1.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>