

Basic Bootstrap CSS Classes

Styling headings and body copy

.h1	.h2	.h3
.h4	.h5	.h6
.small	.lead (style content to stand out)	

Modifying alignment, transformation, and abbreviations

.text-left	.text-right	.text-center
.text-justify	.text-nowrap	.text-lowercase
.text-capitalize	.text-uppercase	
.initialism		

Using blockquotes

<blockquote>	<blockquote> w/ <footer> (for author)
--------------	---------------------------------------

<blockquote> w/ .blockquote-reverse

Working with list styles

.list-unstyled	.list-inline	.dl-horizontal (for dictionary lists)
----------------	--------------	---------------------------------------

Styling Code

<code>

<kbd> (Keyboard shortcut)

<var> (for indicating variables)

<pre> (for multiple lines of code)

<pre> w/ .pre-scrollable (for much longer code)

Basic Bootstrap CSS Classes (cont)

<sample> (sample output from a program)

Notes:

<p><abbr title="United States Air Force" class="initialism"> USAF</abbr></p>
<http://getbootstrap.com/css/#initialism>

<var>y</var> =
 <var>m</var><var>x</var> +
 <var>b</var>

Non-Typography Bootstrap CSS Styles

Working with Bootstrap Buttons

| | | |
|------------------|------------------|------------------|
| .btn btn-default | .btn btn-primary | .btn btn-success |
| .btn btn-info | .btn btn-warning | .btn btn-danger |

Further Bootstrap Button Subclasses

| | | |
|------------|---------|---------------------------------|
| .btn-lg | .btn-sm | .btn-xs |
| .btn-block | .active | disabled="disabled" (attribute) |

Table Styles

.table (use w/ <table> HTML element)

Further Bootstrap Table Subclasses

| | |
|---|-----------------|
| .table-striped | .table-hover |
| .table-condensed | .table-bordered |
| .active | .success .info |
| .warning | .danger |
| .table-responsive (use w/ .container surrounding table) | |

Image Classes

| | | |
|--|-------------|----------------|
| .img-responsive (can use with .center-block) | | |
| .img-rounded | .img-circle | .img-thumbnail |

Helper Classes

| | | |
|-------------|---------------|---------------|
| .text-muted | .text-primary | .text-success |
|-------------|---------------|---------------|

Non-Typography Bootstrap CSS Styles (cont)

| | | |
|-----------------------------------|--------------|---------------|
| .text-warning | .text-danger | .bg-primary |
| .bg-success | .bg-warning | .bg-danger |
| .pull-left | .pull-right | .center-block |
| .clearfix | .show | .hidden |
| .invisible (opacity becomes zero) | | |
| .text-hide | | |

Responsive Utility Classes

VISIBILITY-SIZE(-DISPLAY)

Visibility: visible or hidden

Size: xs, sm, md, lg, print

Display: block, inline, inline-block, print (not necessary if visibility is hidden)

Bootstrap Buttons work with <a>, <button>, <input>

<button class="btn btn-default" disabled="disabled">

.pull-left/right don't work with navigation elements. You must use .navbar-left/right

.text-hide comes in handy when, for example, you want to replace some headers with some images while retaining the text for SEO or semantic purposes