

### Constructing JQL Queries

JIRA 1 Example Clause      project = TEST

JIRA 2 Example Clause      project = TEST AND assignee in (currentuser())

#### Breakdown

Field                      project

Operator                 =

Value                     TEST

Values & Functions      TEST AND assignee = currentUser()

A simple query in JQL (also known as a 'clause') consists of a field, followed by an operator, followed by one or more values or functions. For example:

### Scoping and sorting

**Scoping**      Focusing your query so it pulls the right amount of data so the user sees only the information relevant to the current item at hand.

**Sorting**      Ordering your data such that the most critical set of data is listed first.

Part of a good query is knowing how to get data out of JIRA. The other part is knowing how to engage your team and your customers with the result. Let's start with two concepts that are critical to effective data presentation.

### Fields

Assignee                      Epic Link                      Resolved

Affected version              Filter                          Sprint

Attachments                      Fix version                      Status

Comment                          Issue key                          Summary

Component                          Labels                          Text

Created                          Last viewed                          Time spent

Creator                          Priority                          Voter

Description                          Project                          Watcher

Due                                  Reporter                          *custom field*

A field in JQL is a word that represents a Jira field (or a custom field that has already been defined in Jira).

### Operators

=                                      !=

>                                      <

>=                                      <=

~                                      !~

in                                      not in

is                                      is not

was                                      was not

was in                                      was not in

changed

An operator in JQL is one or more symbols or words that compare the value of a field on its left with one or more values (or functions) on its right, such that only true results are retrieved by the clause. Some operators may use the NOT keyword.



By **Justin Byrne** (justinbyrne)

Published 19th December, 2017.

Last updated 19th December, 2017.

Page 1 of 2.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

<https://apollopad.com>

[cheatography.com/justinbyrne/](https://cheatography.com/justinbyrne/)

[www.byrne-systems.com](https://www.byrne-systems.com)

### Functions

Time	People	Issue
startOfDay/Week/Month/Year	currentLogin()	issueHistory()
endOfDay/Week/Month/Year	currentUser()	openSprints()
lastLogin()		watchedIssues()
now()		myApproval()
		myPending()

A function in JQL appears as a word followed by parentheses, which may contain one or more explicit values or Jira fields.

A function performs a calculation on either specific Jira data or the function's content in parentheses, such that only true results are retrieved by the function, and then again by the clause in which the function is used.

### Reserved characters & words

space (" ")	/	a, and, are, as, at,
+	%	be, but, by, for, if,
.	^	in, into, is, it, no,
,	\$	not, of, on, or, s,
;	#	such, t, that, the, their,
?	@	then, there, these, they,
	[	this, to, was, will, with
*	]	

When using these common characters or words in queries, you need to:

1. Surround them with quote-marks. You can use either single quote-marks (') or double quote-marks (") eg. text ~ "encoding"
2. If you are searching a text field and the character is on the list of reserved characters or words, precede them with two backslashes \

### Term modifiers

Wildcard search	Fuzzy search
Replace single character with ? e.g. te?t	Add to the end of a single term e.g. roam
Replace multiple characters with e.g. win	
Proximity search	Boost term
Add and a number to the end of a phrase in quotes e.g. text "Atlassian jira"~10'	Add with a boost factor (a number) to the end of a search term e.g. atlassian <sup>4</sup> jira

### Word stemming

Field	Add to the beginning of a single term e.g. customize
-------	---



By **Justin Byrne** (justinbyrne)

Published 19th December, 2017.

Last updated 19th December, 2017.

Page 2 of 2.

Sponsored by **ApolloPad.com**

Everyone has a novel in them. Finish Yours!

<https://apollopod.com>