

### 802.1Q Fields

<b>Tag protocol identifier (TPID):</b>	16-bit is field set to 0x8100 to identify the packet as an 802.1Q packet.
<b>Priority code point (PCP):</b>	3-bit field indicates a class of service (CoS) as part of Layer 2 quality of service (QoS) between switches.
<b>Drop eligible indicator (DEI):</b>	This 1-bit field indicates whether the packet can be dropped when there is bandwidth contention.
<b>VLAN identifier (VLAN ID):</b>	This 12-bit field specifies the VLAN associated with a network packet.

### Centralized Forwarding VS Distributed Forwarding

#### \* Centralized Forwarding \*

⇒ When a route processor (RP) engine is equipped with a forwarding engine

#### \* Distributed Forwarding \*

⇒ Forwarding engines are equipped in the line cards

⇒ When a packet is received on the ingress line card, it is transmitted to the local forwarding engine. The forwarding engine performs a packet lookup, and if it determines that the outbound interface is local, it forwards the packet out a local interface. If the outbound interface is located on a different line card, the packet is sent across the switch fabric, also known as the backplane, directly to the egress line card, bypassing the RP.

### VLAN Ranges

<b>VLAN 0</b>	<b>Used for 802.1P Traffic</b> Cannot be modified/deleted
<b>VLAN 1</b>	<b>Default VLAN</b> Cannot be modified/deleted
<b>VLAN 1002 to 1005</b>	<b>Reserve Range</b> Can be modified/deleted
<b>VLAN 1001</b>	<b>Normal Range</b> Can be modified/deleted
<b>VLAN 1006 to 4094</b>	<b>Extended Range</b> Can be modified/deleted



By [justinpam08](#)

[cheatography.com/justinpam08/](https://cheatography.com/justinpam08/)

Published 11th June, 2018.

Last updated 25th February, 2020.

Page 1 of 1.

Sponsored by [Readable.com](#)

Measure your website readability!

<https://readable.com>