

Boiler plate program

```
program name
    imp licit none
    ! module imports go here
    ! local variables go here
    ! code goes here, there
is not main entry point.
end program
```

Module

```
module name
    imp licit none
    use other_module !
import another module
    ! local variables go here
    con tains
    ! functions and subrou -
tines goes here
end module
```

Function

```
! return type goes before the
function
integer function f()
    f = 42 ! the function
name is result variable
end function
```

Subroutine

```
! subroutines does not return a
value
! but they have out parameters
subroutine sub(a, b, c)
    int eger, intent(in) ::
a
    int eger, intent(in) ::
b
    int eger, intent (out)
:: c
    c = a + b
end subroutine
```

Loops

```
do while (logical expr)
    ! Control:
    ! exit for break
    ! cycle for continue
end do
label: do i = start, stop ! ,
step ! (optional)
    ! statements
end do
```

Conditions

```
if (cond) then
    ! ...
else if (cond) then
    ! ...
else
    ! ...
end if
```

Operators

+ -	addition, subtraction
* /	multiplication, division
**	exponentiation
==	equality (numbers)
/=	inequality (numbers)
>, <	greater/less than
>=, <=	greater/less or equal
.eqv.	equality (booleans)
.neqv.	inequality (booleans)
.and., .or., .not.	logical and, or and not.

Native functions

abs(v)	absolute value of v
aimag(z)	imaginary part of z (single prec)
int(v, kind)	truncates toward zero to convert to integer
ceiling(v, kind)	ceiling and convert
floor(v, kind)	floor and convert
modulo(a, p)	polymorphic modulo (sign of p)
cmplx(x, y, kind)	make a complex from floats
conjg(z)	conjugate complex
cos(x), dcos(x), ccos(x)	cosine
sin(x), dsin(x), csin(x)	sine
acos(x), dacos(x)	inverse cosine
asin(x), dasin(x)	inverse sine
dprod(x, y)	x * y as a double
exp(x), dexp(x), cexp(x)	exponential
erf(x), derf(x)	error function
erfc(x), derfc(x)	complementary error function
hypot(a, b)	hypotenuse of x and y (single prec)
log(x), log10(x)	natural and base 10 logarithm
max(a, b, ...), min(a, b, ...)	polymorphic extrema

Native functions (cont)

sum(arr), product(arr),
minval(arr), maxval(arr),
all(arr), any(arr) polymorphic
reduction of
array

sum(arr, dim), product(arr,
dim), minval(arr, dim),
maxval(arr, dim), all(arr,
dim), any(arr, dim) polymorphic
reduction of
array along
axis dim

minloc(arr), maxloc(arr) the coordi-
nates of an
extrema as a
1D array

minloc(arr, dim), maxloc(arr,
dim) the indices of
extrema in
along axis
dim

Data types

logical boolean

integer(k -
ind=1) 8 bits signed integer

integer(k -
ind=4) 32 bits signed
integer

integer(k -
ind=8) 64 bits signed
integer

real(k ind=4) simple precision
float

real(k ind=8) double precision
float

complex(k -
ind=4) simple precision
complex number

complex(k -
ind=8) double precision
complex number

character -
(len=n) string of size n

integer,
dimension(m,
n) 2D array of shape
(m, n)

Derived types

```
type :: name
    integer :: i
    real :: x
    ! more fields
end type
type(some_type) :: obj
! Initialize
obj%field_a = 1
obj%field_b = 0.5
```

