

### Functions construct

The constructs for(), foreach(), and each() can all be used to iterate an object if the object...

- A. implements ArrayAccess
- B. implements Iterator
- C. implements Iterator and ArrayAccess
- D. None of the above

Answer : C

### Functions

Which PHP function is used to validate whether the contents of \$\_FILES['name']['tmp\_name'] have really been uploaded via HTTP, and also save the contents into another folder?

Answer : move\_uploaded\_file(), move\_uploaded\_file

### Functions

Which PHP function sets a cookie and URL encodes its value when sending it to the browser?

Answer: setcookie, setcookie()

### Functions

Which PHP function sets a cookie whose value does not get URL encoded when sending it to the browser?

setrawcookie, setrawcookie()

### Functions

What function can reverse the order of values in an array so that keys are preserved?

- A. array\_flip()
- B. array\_reverse()
- C. rsort()
- D. krsort()
- E. array\_multisort()

Answer: B

### Functions

PHP's array functions such as array\_values() can be used on an object if the object...

- A. implements Traversable
- B. is an instance of ArrayObject
- C. implements ArrayAccess
- D. None of the above

Answer: D

### Functions

You need to escape special characters to use user input inside a regular expression.

Which functions would you use? (Choose 2)

- A. addslashes()
- B. htmlentities()
- C. preg\_quote()
- D. regex\_quote()
- E. quote\_meta()

Answer: C, E

### Functions

Which function can NOT help prevent cross-site scripting? (Choose 2)

- A. addslashes()
- B. htmlentities()
- C. htmlspecialchars()
- D. strip\_tags()
- E. quotemeta()

Answer: A, E

### Functions

Which of these error types may be handled by user defined error handler function?

- A. E\_ERROR
- B. E\_NOTICE
- C. E\_PARSE
- D. E\_WARNING

Answer: A, C



### Functions

You want to allow your users to submit HTML code in a form, which will then be displayed

as real code and not affect your page layout. Which function do you apply to the text, when displaying it? (Choose 2)

- A. strip\_tags()
- B. htmlentities()
- C. htmlspecialchars()
- D. htmlspecialchars()
- E. showhtml()

Answer: B, D

### Functions

You want to parse a URL into its single parts. Which function do you choose?

- A. parse\_url()
- B. url\_parse()
- C. get\_url\_parts()
- D. geturlparts()

Answer: A

### Functions

Which of the following functions are used to escape data within the context of HTML?

(Choose 2)

- A. htmlentities()
- B. addslashes()
- C. stripslashes()
- D. strip\_tags()
- E. htmlspecialchars()

Answer : A,E

### Functions

What will the following function call print?

```
printf("%010.6f", 22);
```

- A. 22
- B. 22.00
- C. 022.000000
- D. 22.000000

Answer : C

### Functions

Which elements does the array returned by the function pathinfo() contain?

- A. root, dir, file
- B. dirname, filename, fileextension
- C. dirname, basename, extension
- D. path, file

Answer: C

### Comparison func and operator

What is the difference between the spaceship operator (<=>) and the strcmp() function?

- A. There is no difference in functionality
- B. strcmp() returns a Boolean value, the spaceship operator a number
- C. strcmp() does a case-intensive comparison, the spaceship operator does not
- D. The spaceship operator returns -1, 0 or 1; strcmp() may return any integer

Answer : D

### Anonymous Functions

Which of the following statements about anonymous functions in PHP are NOT true? (Choose 2)

- A. Anonymous functions can be bound to objects
- B. Anonymous functions created within object context are always bound to that object
- C. Assigning closure to a property of an object binds it to that object
- D. Methods bind() and bindTo() of the Closure object provide means to create closures with different binding and scope
- E. The binding defines the value of \$this and the scope for a closure

Answer: B,C

### Functions

What function allows resizing of PHP's file write buffer?

- A. ob\_start()
- B. set\_write\_buffer()
- C. stream\_set\_write\_buffer()
- D. Change the output\_buffering INI setting via ini\_set() function

Answer: C



### Functions

Which constant must be passed as the second argument to `htmlspecialchars()` to convert single quotes (') to HTML entities?

- A. TRUE
- B. FALSE
- C. ENT\_QUOTES
- D. ENT\_NOQUOTES
- E. ENT\_COMPAT

Answer: C

### Functions

What is the name of the PHP function used to automatically load non-yet defined classes?

- A. `autoload()`
- B. `__autoload()`
- C. `__catch()`
- D. `load()`
- E. `loadClass()`

Answer: B

### Functions

Which PHP function retrieves a list of HTTP headers that have been sent as part of the HTTP response or are ready to be sent?

- A. `header()`
- B. `headers()`
- C. `headers_list()`
- D. `headers_sent()`
- E. `getresponseheaders()`

Answer: C

### Functions

What is the name of the function that allows you register a set of functions that implement user-defined session handling?

- A. `session_set_handler()`
- B. `session_set_storage_handler()`
- C. `session_register_handler()`
- D. `session_set_save_handler()`

Answer: D

### Functions

What function is best suited for extracting data from a formatted string into an array?

- A. `fgetcsv`
- B. `sscanf`
- C. `sprintf`
- D. `strtok`

Answer : C

### Functions

What function can be used to retrieve an array of current options for a stream context?

- A. `stream_context_get_params`
- B. `stream_context_get_default`
- C. `stream_context_get_options`
- D. The 'options' element of the `stream_get_meta_data` return value

Answer : C

### Functions

Which of the following is NOT a valid function declaration?

- A. `function x ($x1= array())`
- B. `function x (A $x1)`
- C. `function x (A $x1 = null)`
- D. `function x ($x1 = $x2)`

Answer : D

### Functions

Which of the following PHP functions can be used to set the HTTP response code? (choose 2)

- A. `header_add()`
- B. `header()`
- C. `http_set_status()`
- D. `http_response_code()`
- E. `http_header_set()`

Answer: B, D



### Functions

Which PHP function is used to validate whether the contents of `$_FILES['name']['tmp_name']` have really been uploaded via HTTP?

Answer : `is_uploaded_file()`, `is_uploaded_file`

### Functions

How do you allow the caller to submit a variable number of arguments to a function?

- A. Using a prototype like function `test(... $parameters)`.
- B. Using a prototype like function `test()` and the function `func_get_args()` inside the function body.
- C. Using a prototype like function `test($parameters[])`.
- D. Using a prototype like function `test()` and the function `get_variable_args()` inside the function body.
- E. This is not possible in PHP.

Answer : B

### Comparison func and operator

What is the difference between the spaceship operator (`<=>`) and the `strcmp()` function?

- A. There is no difference in functionality
- B. `strcmp()` returns a Boolean value, the spaceship operator a number
- C. `strcmp()` does a case-intensive comparison, the spaceship operator does not
- D. The spaceship operator returns -1, 0 or 1; `strcmp()` may return any integer

Answer : D

### Functions

Which of the following functions will allow identifying unique values inside an array?

- A. `array_unique_values`
- B. `array_distinct`
- C. `array_count_values`
- D. `array_intersect`
- E. `array_values`

Answer : C

