

Create/List key pairs

dotenvx init	Create .env and .env.keys in current directory
dotenvx -p test init	Create .env.test and .env.keys for test profile
dotenvx init -g	Create \$HOME/.env.keys for global profiles
dotenvx keypair	Validate and print key pair for .env
dotenvx -p test keypair	Validate and print key pair for .env.test
dotenvx keypair --all	List all global key pairs
dotenvx keypair --import	Import private key

Please use 'cargo binstall dotenvx-rs' to install dotenvx or download it from <https://github.com/linux-china/dotenvx-rs/releases>

encrypt and decrypt for .env files

dotenvx encrypt	Encrypt .env file
dotenvx -p test encrypt	Encrypt .env.test file
dotenvx encrypt --sign	Encrypt and sign .env file
dotenvx verify	Verify the .env file with public key and sign header in the file
dotenvx decrypt	Decrypt .env file
dotenvx -p test decrypt	Decrypt .env.test file
dotenvx decrypt --stdout	Read .env file and print the decrypted items to stdout
dotenvx decrypt --dump	Decrypt .env file and output entries to stdout with JSON format

You can sign an .env file. If somebody modify the .env file, and verification will be failed.

SDKs & CLIs with Dotenvx

dotenvx link .venv/bin/python	Generate python interpreter with Dotenvx support
dotenvx link bin/mysql	Generate mysql cli with .env setup
dotenvx link bin/psql	Generate psql cli with .env setup
dotenvx link bin/mongo	Generate mongo cli with .env setup

SDKs & CLIs with Dotenvx (cont)

dotenvx link bin/redis-cli	Generate redis-cli with .env setup
dotenvx link bin/duckdb	Generate duckdb with .env duckdb setup

Environment variables from .env:

- MYSQL_URL, POSTGRES_URL, DATABASE_URL
- MONGODB_URL
- REDIS_URL

.env file example

```
# ---
# uuid: f7580a c5- 0b2 4-4 385 -b3 ff- 819 225 -
# b687f3
# name: input your name here
# group: demo
# ---
DOTENV _PUBLIC_KEY= " 02b 497...."
# Environment variables. MAKE SURE to ENCRYPT
them before committing to source control
HELLO= encrypted :base64_text
```

.env.key file example

```
# ---
# uuid: 8499c5 c3- cee 3-4 c94 -99 a4- 9c8 6b2 -
# ed5dd9
# name: input your name here
# group: demo
# ---
# Private decryption keys. DO NOT commit to source
control
DOTENV_PRIVATE_KEY =9e 701 8-h ex-text
DOTENV_PRIVATE_KEY_EXAMPLE= a3d 15- hex -
text
```

GitHub Actions setup

```
jobs:
  dot env x-demo:
    run s-on: ubuntu -latest
    steps:
      - uses: action s/c hec kout@v4
      - uses: linux- chi na/ set up- dot env -
x@main
      - run: npm install
      - run: $HOME/.ca rgo /bi n/d otenvx run
-- node index.js
    env:
      DOT ENV _PR IVA TE_KEY: ${{
secret s.D OTE NV_ PRI VAT E_KEY }}
```

Please add DOTENV _PR IVA TE_KEY secret to the Repository secrets first.

If you use act for local GitHub Actions test, please use `act -j dot env x-demo --secret-file .env.keys`.



By [linux_china](#)

cheatography.com/linux-china/

Published 24th July, 2025.

Last updated 19th September, 2025.

Page 1 of 3.

Sponsored by [CrosswordCheats.com](#)

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Get/Set item from .env file

dotenvx get admin	Get ADMIN value from .env file
dotenvx get	GET all key/value pairs from .env file
dotenvx set admin Jackie	SET ADMIN to Jackie in .env file
dotenvx set admin -	SET ADMIN from input
dotenvx set key - < ./private.pem	Set key from text of private.pem file
dotenvx set <key> --clipboard	Set key from clipboard

Please press Ctrl+D on Linux/macOS or Ctrl+Z on Windows to finish input.

Switch profile

dotenvx -p test	Change profile to test
dotenvx encrypt -f .env.test	Change profile to test by .env file name
NODE_ENV=test dotenvx encrypt	Change profile to test by environment

profile's environment variable names: NODE_ENV, RUN_ENV, APP_ENV, SPRING_PROFILES_ACTIVE.

Run command with .env support

dotenvx run -- ./demo.sh	Inject env variables from .env and run ./demo.sh
dotenvx -f prod run -- ./demo.sh	Inject env variables from .env.prod and run ./demo.sh
dotenvx run -- echo '\$HELLO'	Inject env variables from .env to run command line
dotenvx -c 'echo \$HELLO'	Inject env variables from .env and run command line

Please use single quote to wrap variables from .env file.

Rotate key pair for project

dotenvx rotate	Rotate key pair for .env file
dotenvx -p prod rotate	Rotate key pair for .env.prod file
dotenvx rotate -f .env.prod	Rotate key pair for .env.prod file

Global private key management

dotenvx init --global	Generate global private keys in \$HOME/.env.keys
dotenvx -- seal	Encrypt \$HOME/.env.keys, \$HOME/.dotenvx/.env.key.json with your password
dotenvx -- unseal	Decrypt \$HOME/.env.keys.aes, \$HOME/.dotenvx/.env.keys.json.aes with password

Misc

eval \$(dotenvx decrypt -- export)	Export .env items to environment variables
eval \$(dotenvx get hello -- format shell)	Export HELLO from .env items as environment variable
dotenvx ls	List all .env file from current directory recursively
dotenvx -f test ls	List all .env.test file from current directory recursively
dotenvx diff key1,key2	Display keys' values between all .env files
dotenvx diff key1,key2 -- format csv	Display keys' values between all .env files by csv
dotenvx completion -- shell zsh	Output auto-completion script for bash/zsh/fish/powershell

Tips: if you use direnv, and you can add "eval \$(dotenvx decrypt -- export)" to the .envrc file to automatically load .env as the environment variables when you enter the directory.

Node.js(Volat), Bun, Deno with Dotenvx

```
#!/bin/bash
# load .env by dotenvx
eval $( dotenvx decrypt --stdout --format shell )
# Execute bun command with arguments
$HOME/.bun/bin/bun " $@"
#$HOME/.deno/bin/deno " $@"
```

Volta Dotenvx edition: <https://github.com/linux-china/volta/releases/tag/v2.0.2-dotenvx20250830>

Node.js, Bun/Deno script wrapper with Dotenvx: nodew, bunw, denow.

You can create wrapper script for Lua, PHP, Perl with same way.