

### Simple justfile

```
#!/usr/bin/env just --justfile
# hello is recipe's name
hello:
    echo " Hello World! "
```

### default Recipe

```
default: lint build test
# default recipe to display help
information
default:
    @just --list
# if no default recipe, first
recipe will be default
```

### Aliases

```
alias t := test
alias c := check
```

### Settings

```
set shell := ["zsh", "-cu"]
#set shell := ["bu n", " exe c"]
set dotenv -load := true
serv:
    echo " $DA TAB ASE _AD -
DRESS from .env"
set positiona l-a rgu ments :=
true
foo:
    echo $0
    echo $1
```

### Strings - escape with Double-quoted

```
string-with-tab := "\t"
string -wi th- newline := " \n"
escapes := '\t\n \r"\`\'
# this string will evaluate to
`foo\n bar\n`
x := '''
    foo
    bar
    '''
```

### just command line

```
# run recipe
$ just hello param1
# list recipes in alphabetical order
$ just --list
$ just --summary
# Show full information about recipe
just --show test
# select recipes to run interactively
$ just --choose
# shell completion
just --completions zsh
```

### GitHub Actions

```
- uses: extractions/setup-
just@v1
    with:
        jus t-v ersion: 0.10.5
```

### IDE integration

VS Code: <https://marketplace.visualstudio.com/items?itemName=skellock.just>

JetBrains: <https://plugins.jetbrains.com/plugin/18658-just>

### Just module

```
# load bar/justfile,
bar/.justfile, bar.just
mod bar
```

```
just --unstable bar::hello
```

### Recipe with parameters

```
filter PATTERN:
    echo {{PATTERN}}
# param with default value
email address s=' mas ter @ex -
amp le.c om':
    echo {{address}}
# param with expression
test triple =(a rch() + " -un -
kno wn- unk now n"):
    ./test {{triple}}
# variadic param: '+' accept one
or more values
backup +FILES:
    scp {{FILES}}me@exa mpl -
e.com
# variadic param with *: zero or
more values
commit MESSAGE *FLAGS:
    git commit {{FLAGS}} -m "
{{MESSAGE}}"
```

### Recipe with env variable for command

```
# recipe param as env variable
with $ sign
hello $name:
    echo $name
```

### Recipe Dependencies - Before, After & Around

```
# execution sequence: a -> b ->
c -> d
b: a && c d
# execute recipe 'a' around
b:
    echo 'B start!'
    just a
    echo 'B end!'
# depend with params by
expression
default: (build " mai n")
build target:
    @echo 'Building
{{target}}...'

```

### Command annotate: quiet(@), suppress(-), invert(!)

```
hello:
    @ echo " command will not be
echoed "
    - echo " ignore none-zero
exit status and contin ue"
@hello2:
    echo " command will not be
echoed "
# Invert command exit status by
! - shell feature
hello3:
    # if command succee ds(exit
status is 0), exit just
    ! git branch | grep '*'
master'

```

### Recipe with other Languages

```
bash-test:
    #!/usr/bin/env bash
    set -euxo pipefail
    hello='Yo'
    echo " $hello from bash!"

```

### Private Recipes - name starts with \_

```
test: _test-helper
    ./bin/test
# omitted from 'just --list'
_test-helper:
    ./bin/super-secret-test-
helper-stuff

```

### Recipes as shell alias

```
for recipe in `just -f
~/.justfile --summary`; do
    alias $recipe="just -f
~/.justfile -d. $recipe"
done

```

### Recipe with Python venv

```
venv:
    [ -d .venv ] || uv venv
run: venv
    ./venv/bin/python3
main.py

```

### Variable and Substitution

```
version := "0.2.7"
tardir := "awesome-" +
version
tarball := tardir + ".tar.gz"
test:
    echo {{version}}
# set/override variables from
just command line
$ just --set version 1.1.0

```

### Environment variable for commands

```
export RUST_BACKTRACE := "1"
test:
    # will print a stack
trace if it crashes
    cargo test

```

### backtick - capture output from evaluation

```
JAVA_HOME := `jbang jdk home 11`
# backtick code block
stuff := ``
    foo="hello"
    echo $foo "world"
``
done
BRANCH=`git rev-parse --
abbrev-ref HEAD`:
    git checkout master
sloc:
    @echo "`wc -l *.c` lines
of code"
# backtick works anywhere:
string/variable/params

```

### Just functions

```
hello name:
    echo {{os()}}
    echo {{uppercase(name)}}
# function categories
* System Information
* Environment Variables
* Justfile and Justfile
Directory
* String Manipulation
* Path Manipulation
# String contact: (key + " : " +
value)

```

### Conditional expressions: if, loop and while

```
# regular expression match
fo := if "hi" =~ 'h.+' { " -
match" } else { " mismatch" }
test:
    if true; then echo 'True!';
fi
    for file in `ls`; do echo
$file; done

```

### Conditional expressions: if, loop and while (cont)

```
> while `server-is-dead`; do ping -c 1
server; done
foo bar:
    echo {{ if bar == "bar" { "hello" } else { "-
bye" } }}
```

### Attention

```
# Each command line is executed
by a new shell.
# If a command line failed, just
will exit, \
# and subsequent command lines
will not be executed.
change -wo rki ng-dir:
    cd bar && pwd
    # multi-line construct -
escape newline with slash
    if true; then \
        echo 'True!'; \
    fi
# justfile is case insensitive:
Justfile, JUSTFILE etc
# justfile could be hidden:
'.just file'
# Call recipe from sub dir:
`~/app 1/t arg et>$ just build`
```



By **linux\_china**  
[cheatography.com/linux-china/](https://cheatography.com/linux-china/)

Published 22nd December, 2021.  
Last updated 7th April, 2024.  
Page 3 of 3.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>