

### Pandas

```
import pandas as pd

mydataset = { 'cars': ["BMW", "Volvo", "Ford"],
              'passings': [3, 7, 2]
            }
myvar = pd.DataFrame(mydataset) print(myvar)
```

```
      car s   pa ssings
0      BMW           3
1     Volvo           7
2      Ford           2
```

```
df = pd.read_csv('data.csv')
print(df)

df = pd.read_csv(filepath_or_buffer='./testdata.csv',sep=";",dtype=
=string)
```

Pandas is a library used for working with data sets.  
 functions: analyzing, cleaning, exploring, and manipulating data.  
<https://pandas.pydata.org/docs/reference/>  
[https://pandas.pydata.org/docs/reference/api/pandas.read\\_csv.html](https://pandas.pydata.org/docs/reference/api/pandas.read_csv.html)

### PyPDF2

```
from PyPDF2 import PdfFileReader

def text_extractor(path):
    with open(path, 'rb') as f:
        pdf = PdfFileReader(f) # get the first page
        page = pdf.getPage(1)
        print("page : \n ", page)
        print('\n Page type: {}'.format(str(type(page))))

    text = page.extractText()
    print("page text: ", text)

if __name__ == '__main__':
    path = 'filename.pdf' # enter file for input
    text_extractor(path)
```

extract metadata, extract text, split/merge pdfs, rotate pages, encryption:  
<https://www.blog.pythonlibrary.org/2018/06/07/an-intro-to-pypdf2/>

### icecream

code	output
<pre>from icecream import ic  def foo(i):     return i + 333</pre>	ic  foo(123): 456
<pre>d = {'key': {1: 'one'}} ic(d['key'][1])</pre>	ic  d['key'][1]: 'one'
<pre>class klass():     attr = 'yep' ic(klass.attr)</pre>	ic  klass.attr: 'yep'

to use instead of print and log for debugging  
<https://github.com/gruns/icecream>

### Extract Text From HTML Pages / Websites

```
conda install -c conda-forge readability lxml

import requests
from readability import Document
response = requests.get('http://example.com')

doc = Document(response.text)
print(doc.title())

print(doc.summary())
```

#### Example Domain

```
<html><body><div id="readabilityBody">
<div>
<h1>Example Domain</h1>
<p>This domain is for use in illustrative examples in documents.
You may use this
domain in literature without prior coordination or asking for permis-
sion.</p>
<p><a href="https://www.iana.org/domains/example">More inform-
ation...</a></p>
</div>
</body>
</div></body></html>
```

### Beautiful Soup (XML extractor)

**Beautiful Soup is a Python library for pulling data out of HTML and XML files.**

```
conda install -c conda-forge beautifulsoup4

from bs4 import BeautifulSoup
html_doc = str(doc.summary())
soup = BeautifulSoup(html_doc, 'html.parser')

print(html_doc) # prints with tags
print(soup.prettify()) # formats string from html tags

soup = BeautifulSoup(html_doc, features="lxml")
print(soup.get_text())
```

# BeautifulSoup (html\_string, parser\_type), lxml is a python module

#### Example Domain

```
This domain is for use in illustrative examples in documents. You
may use this
domain in literature without prior coordination or asking for permis-
sion.
More information...
```

<https://www.crummy.com/software/BeautifulSoup/bs4/doc/>

**Keywords: assert try except**

```
x = " goo dby e"
```

if condition returns False, AssertionError is raised:

```
assert x == " hel lo"
```

or to add a message to console:

```
assert x == " hel lo", " should be goodby e"
```

#### try except block with AssertionError

```
x = 'hello'
```

```
try:
```

```
    assert x == 'goodbye'
```

```
except:
```

```
    print("An exception occurr ed")
```

(so that the program continues running after the error)

[https://www.w3schools.com/python/ref\\_keyword\\_assert.asp](https://www.w3schools.com/python/ref_keyword_assert.asp)

The assert keyword is used when debugging code. The assert keyword lets you test if a condition in your code returns True, if not, the program will raise an AssertionError.

#### Try / Except / Catch differences

try contains the code that may raise exceptions or errors.

except is used to catch the exceptions and handle them.

catch code is executed only when the corresponding exception is raised.



By **LoiVyen**

[cheatography.com/loivyen/](https://cheatography.com/loivyen/)

Not published yet.

Last updated 8th February, 2023.

Page 1 of 6.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

### One Line Loops

#### examples:

```
for i in range(10): print(i)
print( [i**2 for i in range(10) if i%2==0])
for i in range(10): print(i**2 if i<5 else 0)
print( " Text: ", [token.text for token in doc])
```

### Formatting Strings with Variables

#### Example:

```
quantity = 3
itemno = 567
price = 49.95
myorder = "I will pay {2} dollars for {0} pieces of
item {1}."
print( myorder.format( quantity, itemno, price
))
```

### Read Write Print Files

### Type Casting

#### Get Type from Variable

```
name = "freeCodeCamp"
print("The variable, name is of type:", type(name)
)
```

#### output:

The variable, name is of type: <class 'str'>

#### Specify/Convert Variable Type

```
x = int(1) # x will be 1
y = float( " 2.8 ") # y will be 2.8
z = str(3) # z will be "3"
```

### Regular Expression (or re / regex)

```
import re

re.sub (pa ttern, repl, string, count=0, flags=
0)
# D
result = re.sub ('abc', '', input) # D
result = re.sub ('abc', 'def', input) abc
result = re.sub (r' \s+', ' ', input) # R
result = re.sub ('a bc( def )ghi', r'\1', input) patt
# abc
# Elin
# dup
# whit
# pac
# usir
# wild
# R
# a st
# with
# of it
```

```
re.sea rch (pa ttern, string, flags=0)
re.search("c", "abcdef") # M
re.search("^c", "abcdef") # N
re.search('^X', 'A\nB\nX', re.MUL TILINE) mat
# (beg
# of s
# M
# mul
# (beg
# eac
```

```
re.mat ch( " c", " abc def ") # N
# mat
# (.r
# for
# beg
# of s
```

#### More Info:

<https://docs.python.org/3/library/re.html>  
<https://lzone.de/examples/Python%20re.sub>

## open file and read lines with formatting

[https://www.w3schools.com/python/python\\_regex.asp](https://www.w3schools.com/python/python_regex.asp)

```
with open("t_ext_fil_e.t xt", encoding = 'utf-8') as f:
```

```
    lines = f.readlines() # as a list
    docs = list(nlp(line) for line in lines)
```

### (to spaCy docs)

```
for text in docs: #iterate each list item
    for firsts in text: # iterate each word in list (sentence)
        if firsts.is_sentence_start:
            print(firsts.text)
```

```
doc = [nlp(text.strip()) for txt in lines]
# removes escape sequences
```

### or

```
f = open("H_and_booklist.txt", "r")
print(f.read())
```

```
f = open("demo_file.txt", "r")
print(f.readline()) # read first line
```

```
f = open("demo.txt", 'r', encoding='utf8')
print(f.read()) # ^ another way to strip
```

```
f = open("demo.txt", "r")
for x in f:
```

```
    print(x)
```

### # and/or

```
links.append(x.strip()) # declare arr beforehand; links = []
```

```
f.close() # best to close when done unless first option used
```

## Write Files ('w' overwrites; 'a' appends file)

```
f = open("myfile.txt", "w")
f.write(doclist)
f.close()
```

## List to New Text File:

```
with open("newfile.txt", 'w') as fp:
    for text in doclist:
        # write each item on a new line
        fp.write("%s\n" % text)
    print('Done')
```

[https://www.w3schools.com/python/python\\_file\\_handling.asp](https://www.w3schools.com/python/python_file_handling.asp)

<https://pynative.com/python-write-list-to-file/>

Practice Regex: <https://regex101.com/>

## Dictionary

### Create a dictionary

```
thisdict = {
    "brand": "Ford",
    "model": "Mustang",
    "year": 1964,
    "year": 2020,
    "colors": ["red", "white", "blue"]}
}
```

```
print(thisdict["year"])
```

```
#print dictionary key for 'year'
```

```
#(notice the overwritten output; duplicates are not)
```

Output:

1964

2020

```
print(thisdict)
```

Output:

```
{'brand': 'Ford', 'electric': False, 'year': 1964, 'colors': ['red', 'white', 'blue']}
```



By **LoiVyen**

[cheatography.com/loivyen/](https://cheatography.com/loivyen/)

Not published yet.

Last updated 8th February, 2023.

Page 2 of 6.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

### Dictionary (cont)

#### Alternative way to create dictionary (Constructor)

```
thisdict = dict(brand = "Ford", electric = False, year = 2020, colors = ["red", "white", "blue"])
```

#### Alternate retrievals of key values

```
x = thisdict.get("model")
print(x)
```

Output:

Mustang

or to get dictionary key names and/or values

```
x = thisdict.keys()
```

Output:

```
dict_keys(['brand', 'electric', 'year', 'colors'])
```

```
x = thisdict.values()
```

Output:

```
dict_values(['Ford', False, 2020, ['red', 'white', 'blue']])
```

```
x = thisdict.items() #get all keys & values
```

#### Make changes to dictionary

```
car["colors"] = "red"
```

```
print(x)
```

Output:

```
dict_values(['Ford', 'Mustang', 2020, 'red'])
```

or

```
thisdict.update({"year": 2022})
```

#### check if key/entry exists:

```
if "model" in thisdict:
    print("Yes, this key is in {thisdict} dictionary")
```

#### Remove Items

```
thisdict.pop("model") #removes specified key item
```

```
thisdict.popitem() #removes last inserted* item
```

```
del thisdict["model"] #to remove key item or...
```

```
del thisdict #to delete the entire dictionary
```

#### Loop/Iterations on Dictionaries

### Dictionary (cont)

[https://www.w3schools.com/python/python\\_dictionaries.asp](https://www.w3schools.com/python/python_dictionaries.asp)

**clear()** Removes all the elements

**fromkeys()** Returns dict w/ specified keys and value

**get()** Returns value of specified key

**items()** Returns a tupled list for each key value pair

**keys()** Returns a list of dict keys

**pop()** Removes element of specified key

**popitem()** Removes last inserted key-value pair

**setdefault()** Returns value of specified key

**update()** Updates dict w/ specified key-value pairs

**values()** Returns list of all values in dict

```

for x in thisdict:
    print(thisdict[x])
    #print each value in dict per line

for x in thisdict.values():
    print(x)
    #print values of dictionary

for x in thisdict.keys():
    print(x)
    #print keys of dictionary

for x, y in thisdict.items():
    print(x)
    #loop through both keys and values

```

### Nested Dictionary

```

child1 = {
    "name" : "Emil",
    "year" : 2004
}
child2 = {
    "name" : "Tobias",
    "year" : 2007
}
child3 = {
    "name" : "Linus",
    "year" : 2011
}

myfamily = {
    "child1" : child1,
    "child2" : child2,
    "child3" : child3
}

print(myfamily["child2"]["name"])

```

Output:

Tobias

### Other uses with Dictionary

```

No. of components: len(thisdict)
Confirm dict data type: type(thisdict)
Make copy of dictionary: mydict = thisdict.copy()

```



By **LoiVyen**  
[cheatography.com/loivyen/](https://cheatography.com/loivyen/)

Not published yet.  
 Last updated 8th February, 2023.  
 Page 3 of 6.

Sponsored by **CrosswordCheats.com**  
 Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>