

Core Commands

archive-dump <i>(ard, archive-backup, arb)</i>	Backup your code, files, and database into a single file.
archive-restore <i>
arr</i>	Expand a site archive into a Drupal web site.
cache-clear <i>cc</i>	Clear a specific cache, or all drupal caches.
cache-get <i>cg</i>	Fetch a cached object and display it.
cache-set <i>cs</i>	Cache an object expressed in JSON or var_export() format.
core-config <i>conf, config</i>	Edit drushrc, site alias, and Drupal settings.php files.
core-cron <i>cron</i>	Run all cron hooks in all active modules for specified site.
core-execute <i>exec, execute</i>	Execute a shell command. Usually used with a site alias.
core-quick-drupal <i>qd</i>	Download, install, serve and login to Drupal with minimal configuration and dependencies.
core-rsync <i>rsync</i>	Rsync the Drupal tree to/from another server using ssh.

Core Commands (cont)

core-status <i>status, st</i>	Provides a birds-eye view of the current Drupal installation, if any.
core-topic <i>topic</i>	Read detailed documentation on a given topic.
drupal-directory <i>dd</i>	Return path to a given module/theme directory.
help	Print this help message. See <code>drush help help</code> for more options.
image-flush <i>image--flush</i>	Flush all derived images for a given style.
php-eval <i>eval, ev</i>	Evaluate arbitrary php code after bootstrapping Drupal (if available).
php-script	Run php script(s).
search-index	Index the remaining search items without wiping the index.
search-reindex	Force the search index to be rebuilt.
search-status	Show how many items remain to be indexed out of the total.

Core Commands (cont)

self-update <i>selfu-pdate</i>	Check to see if there is a newer Drush release available.
shell-alias <i>sha</i>	Print all known shell alias records.
site-alias <i>sa</i>	Print site alias records for all known site aliases and local sites.
site-install <i>si</i>	Install Drupal along with modules/themes/configuration using the specified install profile.
site-ssh <i>ssh</i>	Connect to a Drupal site's server via SSH for an interactive session or to run a shell command
site-upgrade <i>sup</i>	Run a major version upgrade for Drupal (e.g. Drupal 6 to Drupal 7). A copy of the site is made, and then upgraded; the source site is not changed.
test-clean	Clean temporary tables and files.
test-run	Run tests. Note that you must use the --uri option.



By **lopper69**

cheatography.com/lopper69/

Not published yet.

Last updated 13th May, 2016.

Page 1 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Core Commands (cont)

`updatedb` Apply any database updates required (as with running `update.php`).

`variable--delete` Delete a variable.

`variable-get` Get a list of some or all site variables and values.

`variable-set` Set a variable.

`version` Show drush version.

`watchdog-delete` Delete watchdog messages.

`watchdog-list` Show available message types and severity levels. A prompt will ask for a choice to show watchdog messages.

`watchdog-show` Show watchdog messages.

Field commands

`field--clone` Clone a field and all its instances.

`field--create` Create fields and instances. Returns urls for field editing.

`field--delete` Delete a field and its instances.

`field-info` View information about fields, `field_types`, and widgets.

`field--update` Return URL for field editing web page.

Project manager commands

`pm-disable` Disable one or more extensions (modules or themes).

`pm-download` Download projects from `drupal.org` or other sources.

`pm-enable` Enable one or more extensions (modules or themes).

`pm-info` Show detailed info for one or more extensions (modules or themes).

`pm-list` Show a list of available extensions (modules and themes).

`pm-refresh` Refresh update status information.

`pm-releases` Print release notes for given projects.

`pm-releases` Print release information for given projects.

`pm-uninstall` Uninstall one or more modules.

`pm-update` Update Drupal core and contrib projects and apply any pending database updates (Same as `pm-updatecode + updatedb`).

`pm-updatecode` Update Drupal core and contrib projects to latest recommended releases.

SQL commands

`sql-cli` Open a SQL command-line interface using Drupal's credentials.

`sql-connect` A string for connecting to the DB.

SQL commands (cont)

`sql-drop` Drop all tables in a given database.

`sql-dump` Exports the Drupal DB as SQL using `mysqldump` or equivalent.

`sql-query` Execute a query against the site database.

`sql-sync` Copy and import source database to target database. Transfers via `rsync`

User commands

`user-add-role` Add a role to the specified user accounts.

`user-block` Block the specified user(s).

`user-cancel` Cancel a user account with the specified name.

`user-create` Create a user account with the specified name.

`user-information` Print information about the specified user(s).

`user-login` Display a one time login link for the given user account (defaults to uid 1).

`user-password` (Re)Set the password for the user account with the specified name.

`user-remove-role` Remove a role from the specified user accounts.

`user-unblock` Unblock the specified user(s).



By **opper69**
cheatography.com/opper69/

Not published yet.
Last updated 13th May, 2016.
Page 2 of 3.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
<http://crosswordcheats.com>

All commands in devel

devel-download	Downloads the FirePHP library from http://firephp.org/ .
devel-reinstall	Disable, Uninstall, and Install a list of projects.
devel-token	List available tokens
fn-hook	List implementations of a given hook and explore source of specified one.
fn-view	Show the source of specified function or method.

Global Options

Global Options (see drush topic core-global-options for the full list)

-r <path>, --root=<path>	Drupal root directory to use (default: current directory).
-l http://example.com:8888, --uri=http://example.com:8888	URI of the drupal site to use (only needed in multisite environments or when running on an alternate port).
-v, --verbose	Display extra information about the command.
-d, --debug	
-y, --yes	Display even more information, including internal messages.
-n, --no	Assume 'yes' as answer to all prompts.

Global Options (cont)

-s, --simulate	Assume 'no' as answer to all prompts.
-p, --pipe	Simulate all relevant actions (don't actually change the system).
-h, --help	Emit a compact representation of the command for scripting.
--	This help system.
version	
--php	Show drush version.
-ia, --interactive	The absolute path to your PHP interpreter, if not 'php' in the path.
	Force interactive mode for commands run on multiple targets (e.g. <code>drush @site1,@site2 cc --ia</code>).



By **lopper69**
cheatography.com/lopper69/

Not published yet.
Last updated 13th May, 2016.
Page 3 of 3.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
<http://crosswordcheats.com>