

Creacion back up Completo

```
ALTER DATABASE [nombre_base] SET
RECOVERY FULL
BACKUP DATABASE [nombre_base]
TO DISK = 'c:/direccion.n.bak'
WITH FORMAT,
MEDIANAME = 'nombre_grupo_backup',
NAME = 'nombre_backup';
```

Creacion back up Diferencial

```
RESTORE DATABASE [nombre_base]
FROM DISK = 'C:\direccion -
n.bak'
WITH DIFFERENTIAL;
```

Creacion back up LOG

```
BACKUP LOG [nombre_base] TO DISK
= 'C:\direccion.bak';
```

Restauracion de backup Completo

```
use master;
```

```
RESTORE DATABASE [nueva_base]
FROM DISK = 'C:\direccion.bak'
WITH RECOVERY;
```

Restauracion de backup Completo

```
use master;
RESTORE DATABASE [nueva_base]
FROM DISK = 'C:/direccion_f -
ull.bak'
WITH RECOVERY;
```

Restauracion de backup LOG

```
use master;
RESTORE DATABASE [nueva_base]
FROM DISK = 'C:/direccion_f -
ull.bak'
WITH NORECOVERY;
RESTORE LOG [nueva_base]
FROM DISK = 'C:/direccion_l -
og1.bak'
WITH NORECOVERY;
RESTORE DATABASE [nueva_base]
WITH RECOVERY;
```

Modelos de recuperacion

```
ALTER DATABASE [nombre_base] SET
RECOVERY SIMPLE;
```

```
ALTER DATABASE [nombre_base] SET
RECOVERY FULL;
```

```
ALTER DATABASE [nombre_base] SET
RECOVERY BULK_LOGGED;
```



By **marucci.mauro**

cheatography.com/marucci-mauro/

Not published yet.

Last updated 14th November, 2023.

Page 1 of 1.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>