

### Rows - Grid System

Rows are in `.container` or `.container-fluid`

### Columns

|                       |        |           |
|-----------------------|--------|-----------|
| <code>.col-xs-</code> | Always | Full      |
| <code>.col-sm-</code> | >768   | 750 wide  |
| <code>.col-md-</code> | >992   | 970 wide  |
| <code>.col-lg-</code> | >1200  | 1170 wide |

### Resets, Offsets, Pushes, Pulls

`.clearfix`

`.col-xs-offset- (sm, md, lg)`

### Nest using a .row inside a col

`.col-xs-push- (sm, md, lg)`

`.col-xs-pull- (sm, md, lg)`

`.visible-xs (sm, md, lg)`

`.hidden-xs (sm, md, lg)`

`.visible-print`

`.hidden-print`

### Grid Variables

|                                      |       |
|--------------------------------------|-------|
| <code>@grid-columns:</code>          | 12    |
| <code>@grid-gutter-width:</code>     | 30px  |
| <code>@grid-float-breakpoint:</code> | 768px |

### Using Grid Mixin CSS

```
.wrapper { .make-row(); }
.content-main { .make-lg-column(8); }
.content-secondary {
  .make-lg-column(3);
  .make-lg-column-offset(1);
}
```

### Using Grid Mixin HTML

```
<div class="wrapper">
<div class="content-main">...</div>
<div class="content-secondary">...</div>
</div>
```

### Typography

`.h1` `.h2` `.h3`

`.h4` `.h5` `.h6`

`.small` `<small>` `.lead`

`@font-size-base` | `@line-height-base`

### Align

`.text-left` `.text-right`

`.text-center` `.text-justify`

### Text Helpers

`.text-muted` `.text-primary`

`.text-success` `.text-info`

`.text-warning` `.text-danger`

`.bg-primary` `.bg-success`

`.bg-info` `.bg-warning`

`.bg-danger`

`.text-hide` `.sr-only`

### Lists

`.list-unstyled` `.list-inline`

### Descriptions

`<dl> <dt>...</dt> <dd>...</dd> </dl>`

`.dl-horizontal`

### Images

`.img-responsive` (max-width:100%, height:auto)

`.img-rounded`

`.img-circle`

`.img-thumbnail` (double border)

### Forms

#### NEED TO DO

### Buttons

`<button type="button" class="btn btn-default">Default</button>`

`<a href="#" class="btn btn-primary btn-lg active" role="button">Primary link</a>`

### Button Classes

`.btn-default` `.btn-primary`

`.btn-success` `.btn-info`

`.btn-warning` `.btn-danger`

`.btn-link` (to look like a link)

`.btn-lg` `.btn-sm`

`.btn-xs` `.btn-block`

`.active` (A tag) `.disabled` (A tag)

`disabled="disabled"`

### Labels

`.label` `.label-default`

primary, success, info, warning, danger

`<span class="label label-default">New</span>`

### Badge

`<span class="badge">42</span>`

### Alerts


`.alert` `.alert-success`

success, info, warning, or danger

`.alert-dismissible`

`<button type="button" class="close" data-dismiss="alert" aria-hidden="true">&times;</button>`

`<a href="#" class="alert-link">...</a>`



By **John Mason** (masonjo)  
[cheatography.com/masonjo/](http://cheatography.com/masonjo/)  
[www.e-rehab.com](http://www.e-rehab.com)

Published 29th April, 2014.  
 Last updated 11th May, 2016.  
 Page 1 of 3.

Sponsored by **Readable.com**  
 Measure your website readability!  
<https://readable.com>

### Tables

`.table`                    `.table-striped`

`.table-bordered`        `.table-hover`

`.table-condensed`

`.table-responsive`

Wrap `.table` in `.table-responsive`

```
<div class="table-responsive">
```

```
  ...table
```

```
</div>
```

### Rows or Cells

`.active`            `.success`            `.info`

`.warning`          `.danger`

### Tags

### Tags (cont)

#### Clear Floats

`.clearfix`

#### Center Block (*mixin also*)

`.center-block` (`display:block`, `margin`  
`auto`) | `.center-block()`;

#### Show (*mixin also*)

`.show` | `.show()`;

#### Hide (*mixin also*)

`.hide` | `.hide()`;

#### Glyphicons

```
<span class="glyphicon glyphicon-search"></span>
```

## abbr

```
<abbr title="attribute">attr</abbr>
```

## address

```
<address> <strong>Twitter, Inc.</strong>
<br> 795 Folsom Ave, Suite 600<br>
San Francisco, CA 94107<br> <abbr
title="Phone">P:</abbr> (123) 456-7890
</address>
```

## blockquote

```
<blockquote> <p>Lorem ipsum dolor sit
amet, consectetur adipiscing elit. Intege-
r</p> </blockquote>
```

## blockquote footer

```
<footer>Someone famous in <cite title="-
Source Title">Source Title</cite></foot-
er>
```

## blockquote right justify

```
.blockquote-reverse
```

## code

```
<code>&lt;section&gt;</code>
```

## kbd Keyboard Entry

```
<kbd>cd</kbd>
```

## .pre-scrollable

Max Height 350px box, with y-axis scrollbar. Used with **pre** tag

## close button

```
<button type="button" class="close" aria-
hidden="true">&times;</button>
```

## Caret

```
<span class="caret"></span>
```

## Floats

```
.pull-left .pull-right
```

## Float Mixin

```
.element { .pull-left(); }
```



By **John Mason** (masonjo)  
cheatography.com/masonjo/  
www.e-rehab.com

Published 29th April, 2014.  
Last updated 11th May, 2016.  
Page 2 of 3.

Sponsored by **Readable.com**  
Measure your website readability!  
<https://readable.com>